

Exxon Univis N32

INGREDIENTS	CAS NO	%	8HR OEL
paraffinic distillate, heavy, hydrotreated (severe)	64742-54-7.	>90	5 mg/m3
proprietary additives	Not Available	<10	-
paraffinic distillate, heavy, solvent-dewaxed (severe)	64742-65-0.	}	5 mg/m3

UN No: **Not Applicable**
 Hazchem Code: **Not Applicable**
 DG Class: **None**
 Subsidiary Risk: **None**
 Packing Group: **None**
 Poisons Schedule: **Not Applicable**



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION



Acute Health Effects:

Vapours may cause drowsiness and dizziness.

PRECAUTIONS FOR USE



Appropriate engineering controls:	General Exhaust Ventilation adequate.
Glasses:	Not normally required
Gloves:	When handling larger quantities: PVC chemical resistant type.
Respirator:	Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
Storage and Transportation:	Store in cool, dry, protected area. Dispose of this material and its container at hazardous or special waste collection point. Keep out of reach of children.
Fire/Explosion Hazard:	Toxic smoke/fumes in a fire. Dispose of this material and its container at hazardous or special waste collection point.

PROPERTIES

Liquid
Combustible.

EMERGENCY



FIRST AID

Swallowed:	Give water (if conscious). Seek medical advice.
Eye:	Wash with running water.
Skin:	Remove contaminated clothing. Wash with soap & water.
Inhaled:	Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.
Advice To Doctor:	Emesis generally unnecessary. Debride for subcutaneous injection.
Fire Fighting:	Foam.
Spills and Disposal:	Eliminate ignition sources. Absorb with dry agent. Stop leak if safe to do so. Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS

x — Must not be stored together