

# PETROLEUM ETHER

**INGREDIENTS CAS NO** % 8HR OEL 8032-32-4 >99 petroleum ether



UN No: 1268 Hazchem Code: 3YE DG Class: 3

Subsidiary Risk: Not Applicable

Packing Group: I Poisons Schedule: S5

## NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

## **HEALTH HAZARD INFORMATION**





**Acute Health** Effects: HARMFUL-May cause lung damage if swallowed. Vapours may cause drowsiness and dizziness.

### PRECAUTIONS FOR USE

















Appropriate engineering controls:	Local Exhaust Ventilation recommended.
Glasses:	Consider chemical goggles.
Respirator:	Type AX Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
Storage and Transportation:	Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report. Keep out of reach of children. Keep container in a well ventilated place. Keep away from food, drink and animal feeding stuffs. Keep away from sources of ignition. No smoking.
Fire/Explosion Hazard:	HIGHLY FLAMMABLE. Vapours/gas heavier than air. Toxic smoke/fumes in a fire. In case of fire and/or explosion, DO NOT BREATHE FUMES.
Environment:	Toxic to aquatic organisms.  May cause long-term adverse effects in the

aquatic environment.

# **PROPERTIES**









Does not mix with water.

Floats on water. Extremely flammable.

## **EMERGENCY**











## **FIRST AID**

Swallowed:	Give water (if conscious). Seek medical advice. Do NOT give milk or oil. Do NOT give alcohol.
Eye:	Wash with running water.
Skin:	Remove contaminated clothing. Wash with soap & water.
Inhaled:	Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.
Advice To Doctor:	Evaluate for respiratory distress. Consider lavage with cuffed tube. NO adrenalin.
Fire Fighting:	Keep containers cool. Foam.
Spills and	Spilled liquid has low temperature and evaporates quickly.  Eliminate ignition sources.  Consider evacuation.  Prevent from entering drains.  Contain spillage by any means.
Disposal:	Control vapour with water spray/ fog. Absorb with dry agent. Stop leak if safe to do so.

## SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS











this material, use water and detergent.

This material and its container must be disposed of

To clean the floor and all objects contaminated by

Explosive

Toxic Radioactive Oxidizing x x x x

in a safe way.

- Must not be stored together