

## TANKGUARD MIL TC COMP.A PAINT (YELLOW)

INGREDIENTS	CAS NO	%	8HR OEL
N-methyl-2-pyrrolidone	872-50-4	2.5-10	103 mg/m3
methyl isobutyl carbinol	108-11-2	<2.5	104 mg/m3
xylene	1330-20-7	<2.5	350 mg/m3
bisphenol A/ diglycidyl ether polymer, high molecular weight	25068-38-6	25-50	-



UN No: 1263  
 Hazchem Code: 3Y  
 DG Class: 3  
 Subsidiary Risk: **Not Applicable**  
 Packing Group: III  
 Poisons Schedule: **Not Applicable**



## NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

## HEALTH HAZARD INFORMATION



**Acute Health Effects:** Irritating to eyes and skin.  
 May cause SENSITISATION by skin contact.

**Chronic Health Effects:** May cause harm to the unborn child.  
 \* – limited evidence

## PRECAUTIONS FOR USE



**Appropriate engineering controls:** Local Exhaust Ventilation recommended.

**Glasses:** Consider chemical goggles.

**Gloves:** 1.PE/EVAL/PE 2.BUTYL 3.PVA

**Respirator:** Type AK Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

**Storage and Transportation:** Store in cool, dry, protected area.  
 Restrictions on Storage apply. Refer to Full Report.

**Fire/Explosion Hazard:** Flammable.  
 Toxic smoke/fumes in a fire.

**Environment:** Toxic to aquatic organisms.  
 May cause long-term adverse effects in the aquatic environment. Use appropriate container to avoid environmental contamination.  
 Avoid release to the environment. Refer to special instructions/Safety data sheets.

## PROPERTIES



Liquid.  
 Mixes with water. Flammable.

## EMERGENCY



## FIRST AID

<b>Swallowed:</b>	Give water (if conscious). Seek medical advice. Do NOT give milk or oil. Do NOT give alcohol.
<b>Eye:</b>	Wash with running water.
<b>Skin:</b>	Remove contaminated clothing. Wash with soap & water.
<b>Inhaled:</b>	Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.
<b>Advice To Doctor:</b>	Treat symptomatically. Evaluate for respiratory distress. Consider lavage with cuffed tube. NO adrenalin.
<b>Fire Fighting:</b>	Water spray/ fog.  Eliminate ignition sources. Prevent from entering drains.
<b>Spills and Disposal:</b>	Contain spillage by any means. Absorb with dry agent. Stop leak if safe to do so.

## SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Explosive Toxic Radioactive Oxidizing

x — Must not be stored together