

NC SANDING SEALER CLEAR

INGREDIENTS	CAS NO	%	8HR OEL
toluene	108-88-3	<10	191 mg/m3
xylene	1330-20-7	<3	350 mg/m3
ethanol	64-17-5	<3	1880 mg/m3
n-butanol	71-36-3	<60	N/A



UN No: 1263
 Hazchem Code: 3YE
 DG Class: 3
 Subsidiary Risk: **Not Applicable**
 Packing Group: II
 Poisons Schedule: **Not Applicable**



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION



Acute Health Effects:

Harmful by inhalation and if swallowed.
 Irritating to respiratory system and skin.
 Risk of serious damage to eyes.
 Vapours may cause drowsiness and dizziness.

Chronic Health Effects:

Harmful: danger of serious damage to health by prolonged exposure through inhalation and if swallowed.
 Possible risk of harm to the unborn child.

* – limited evidence

PROPERTIES



Liquid.

Does not mix with water. Highly flammable.

EMERGENCY



FIRST AID

Swallowed:

Give water (if conscious). Seek medical advice.
 Do NOT give milk or oil.
 Do NOT give alcohol.

Eye:

Wash with running water (15 mins). Medical attention.

Skin:

Remove contaminated clothing. Wash with soap & water.

Inhaled:

Fresh air. Rest, keep warm. If breath shallow, give oxygen. Medical attention.

Advice To Doctor:

Evaluate for respiratory distress. Consider lavage with cuffed tube. NO adrenalin.

Fire Fighting:

Keep containers cool.
 Foam.

Spills and Disposal:

Spilled liquid has low temperature and evaporates quickly.
 Eliminate ignition sources.
 Consider evacuation.
 Prevent from entering drains.
 Contain spillage by any means.
 Control vapour with water spray/ fog.
 Absorb with dry agent.
 Stop leak if safe to do so.

PRECAUTIONS FOR USE



Appropriate engineering controls:

Local Exhaust Ventilation recommended.

Glasses:

Consider chemical goggles.

Gloves:

1.PE/EVAL/PE 2.NITRILE, PVC

Respirator:

Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Storage and Transportation:

Store in cool, dry, protected area.
 Restrictions on Storage apply. Refer to Full Report.

Fire/Explosion Hazard:

HIGHLY FLAMMABLE.
 Toxic smoke/fumes in a fire.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Flammable Explosive Toxic Radioactive Oxidizing

x

x

x

x

x

x — Must not be stored together