

Axalta Coating Imron AF700 BC

INGREDIENTS	CAS NO	%	8HR OEL
amyl methyl ketone	110-43-0	4-15	233 mg/m3
n-butyl acetate	123-86-4	4-15	713 mg/m3
ethyl acetate	141-78-6	1-4	720 mg/m3
heptane	142-82-5	1-4	1640 mg/m3



UN No: 1263 Hazchem Code: •3YE

DG Class: 3

Subsidiary Risk: Not Applicable

Packing Group: II

Poisons Schedule: Not Applicable



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION











HARMFUL-May cause lung damage if swallowed. Vapours may cause drowsiness and dizziness.

Chronic **Health Effects:** May cause CANCER by inhalation.

Repeated exposure may cause skin dryness and cracking.

* - limited evidence

PRECAUTIONS FOR USE













Appropriate engineering controls:

Local Exhaust Ventilation recommended.

Glasses:

Consider chemical goggles.

Gloves:

1.PVDC/PE/PVDC 2.PE/EVAL/PE

Respirator:

Type AX Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report. Use only in

Storage and Transportation: well ventilated areas. Take precautionary measures against static discharges. Dispose of this material and its container at hazardous or special waste collection point. Keep out of reach of children. Keep container in a well ventilated place. Keep away from food, drink and animal feeding stuffs. Keep away from sources of ignition. No smoking.

Fire/Explosion Hazard:

HIGHLY FLAMMABLE. Vapours/gas heavier than air. Toxic smoke/fumes in a fire. Use only in well ventilated areas. Take precautionary measures against static discharges. Dispose of this material and its container at hazardous or special waste collection point. In case of fire and/or explosion, DO NOT BREATHE FUMES.

PROPERTIES







Liquid. Mixes with water. Highly flammable.









FIRST AID

Swallowed:	Give water (if conscious). Seek medical advice.
Eye:	Wash with running water.
Skin:	Remove contaminated clothing. Wash with soap & water.
Inhaled:	Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.
Advice To Doctor:	Treat symptomatically.
Fire Fighting:	Keep containers cool. Water spray/ fog.
	Eliminate ignition sources. Consider evacuation. Prevent from entering drains. Contain spillage by

Spills and Disposal: any means. Absorb with dry agent. Stop leak if safe to do so. Use only in well ventilated areas. Take precautionary measures against static discharges. Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS









Explosive

Toxic Х

Radioactive Oxidizing Х

- Must not be stored together