

Well Flow Hogwash

INGREDIENTS	CAS NO	%	8HR OEL
distillates, petroleum, light, hydrotreated	64742-47-8	<40	5 mg/m3
C5-20 paraffins	64771 -72-8	<10	72 mg/m3
ethylene glycol monobutyl ether	111-76-2	<10	96.9 mg/m3
tetrasodium pyrophosphate	7722-88-5	<5	5 mg/m3



UN No: 1993 Hazchem Code: •3Y DG Class: 3

Subsidiary Risk: Not Applicable

Packing Group: III

Poisons Schedule: Not Applicable



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION















Irritating to eyes and skin.

HARMFUL-May cause lung damage if swallowed. Vapours may cause drowsiness and dizziness.

Chronic **Health Effects:** Possible risk of impaired fertility. Repeated exposure may cause skin dryness and

cracking.

* - limited evidence

PRECAUTIONS FOR USE

















Appropriate engineering controls:

Local Exhaust Ventilation recommended.

Glasses:

Consider chemical goggles.

Gloves:

1.BUTYL 2.PE/EVAL/PE 3.NITRILE

Respirator:

Type AX Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88

or national equivalent)

Storage and

Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report.

Transportation:

Flammable.

Fire/Explosion Hazard:

Toxic smoke/fumes in a fire.

PROPERTIES



Flammable.

EMERGENCY









FIRST AID

Give water (if conscious). Seek medical advice. Swallowed: Do NOT give milk or oil.

Do NOT give alcohol.

Wash with running water. Eye:

Remove contaminated clothing. Wash with soap & Skin:

Fresh air. Rest, keep warm. If breathing shallow, Inhaled:

give oxygen. Medical attention.

Advice To Evaluate for respiratory distress. Consider lavage

with cuffed tube. NO adrenalin. Doctor:

Fire Fighting: Foam.

Spills and

Eliminate ignition sources. Prevent from entering drains.

Disposal: Contain spillage by any means.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS









Explosive Toxic

Radioactive Oxidizing

х Х - Must not be stored together