

VERSATEC CLEAR DISPERSANT

INGREDIENTS	CAS NO	%	8HR OEL
naphtha petroleum, heavy, hydrotreated	64742-48-9	>60	-
aromatic hydrocarbons	63231-51-6	<0.05	-



UN No: 1993 Hazchem Code: •3Y DG Class: 3

Subsidiary Risk: Not Applicable

Packing Group: III Poisons Schedule: S5



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ **3**: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION







Acute Health Effects: HARMFUL-May cause lung damage if swallowed. Vapours may cause drowsiness and dizziness.

Repeated exposure may cause skin dryness and Chronic cracking. **Health Effects:**

* - limited evidence

PRECAUTIONS FOR USE





Appropriate

Hazard:











engineering controls:	Local Exhaust Ventilation recommended.
Glasses:	Consider chemical goggles.
Gloves:	PVC chemical resistant type.
Respirator:	Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
Storage and Fransportation:	Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report.
Fire/Explosion	Flammable. Vapours/gas heavier than air.

Toxic smoke/fumes in a fire.

PROPERTIES







Does not mix with water. Floats on water.Flammable.

EMERGENCY









FIRST AID

Give water (if conscious). Seek medical advice.

Remove contaminated clothing. Wash with soap &

Swallowed: Do NOT give milk or oil.

Do NOT give alcohol.

Eye: Wash with running water.

Skin: water.

Fresh air. Rest, keep warm. If breathing shallow, Inhaled:

give oxygen. Medical attention.

Evaluate for respiratory distress. Consider lavage **Advice To**

with cuffed tube. NO adrenalin. Doctor:

Fire Fighting: Foam.

> Eliminate ignition sources. Spills and Prevent from entering drains. Disposal:

Contain spillage by any means.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS









Radioactive Oxidizing

Toxic X

х х