


Super Demon Air Set Wet (Refractories)

INGREDIENTS	CAS NO	%	8HR OEL
silica crystalline - quartz	14808-60-7	6.9	0.1 mg/m3
silica amorphous	7631-86-9	45	10 mg/m3
aluminium oxide	1344-28-1.	41.5	10 mg/m3

UN No: **Not Applicable**
 Hazchem Code: **Not Applicable**
 DG Class: **Not Applicable**
 Subsidiary Risk: **Not Applicable**
 Packing Group: **Not Applicable**
 Poisons Schedule: **Not Applicable**



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION

PRECAUTIONS FOR USE



Appropriate engineering controls:	Local Exhaust Ventilation recommended.
Glasses:	Consider chemical goggles.
Gloves:	PVC chemical resistant type.
Respirator:	Type AX Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
Storage and Transportation:	Store in cool, dry, protected area.
Fire/Explosion Hazard:	Toxic smoke/fumes in a fire.

PROPERTIES

Does not burn.

EMERGENCY



FIRST AID

Swallowed:	Rinse mouth with water.
Eye:	Wash with running water. For discomfort seek medical advice.
Skin:	Wash with soap
Inhaled:	Fresh air. Rest, keep warm.
Advice To Doctor:	Deferoxamine is preferred chelator. Supportive care. "metal fume fever". Remove from exposure. Treatment is supportive.
Fire Fighting:	Keep surrounding area cool. Water spray/fog.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS

x — Must not be stored together