

International Interzone 954 Part B

INGREDIENTS	CAS NO	%	8HR OEL
methyl isobutyl ketone	108-10-1	2.5-10	205 mg/m3
benzene-1,3-dimethanamine	1477-55-0	10-25	N/A
benzyl alcohol	100-51-6	10-25	-
isophorone diamine	2855-13-2	10-25	-



UN No: **3066**
 Hazchem Code: **2X**
 DG Class: **8**
 Subsidiary Risk: **Not Applicable**
 Packing Group: **II**
 Poisons Schedule: **S5**



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION



Acute Health Effects:

Harmful by inhalation and if swallowed.
 Causes burns.
 Risk of serious damage to eyes.
 May cause SENSITISATION by skin contact.
 Vapours may cause drowsiness and dizziness.

PRECAUTIONS FOR USE



Appropriate engineering controls:

General Exhaust Ventilation adequate.

Glasses:

Consider chemical goggles.
 Consider full face-shield.

Gloves:

1.PE/EVAL/PE 2.PVA 3.TEFLON

Respirator:

Type AK-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Storage and Transportation:

Store in cool, dry, protected area.
 Restrictions on Storage apply. Refer to Full Report.
 Keep locked up.
 Keep out of reach of children.
 Keep away from living quarters.
 Keep away from food, drink and animal feeding stuffs.

Fire/Explosion Hazard:

Vapours/gas heavier than air.
 Toxic smoke/fumes in a fire.

Environment:

Harmful to aquatic organisms.
 May cause long-term adverse effects in the aquatic environment.

PROPERTIES



Liquid.
 Does not mix with water.
 Sinks in water.
 Corrosive.
 Alkaline/Combustible.

EMERGENCY



FIRST AID

Swallowed:

Give water (if conscious). URGENT MEDICAL ATTENTION.

Eye:

Wash with running water (15 mins). Medical attention.

Skin:

Flood body with water. Remove contaminated clothing. Wash with water

Inhaled:

Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.

Advice To Doctor:

Supportive care. Irrigate eyes with saline. Supportive care.

Fire Fighting:

Water spray/ fog.
 Foam - alcohol type.

Spills and Disposal:

Eliminate ignition sources.
 Prevent from entering drains.
 Contain spillage by any means.
 Absorb with dry agent.
 Stop leak if safe to do so.
 This material and its container must be disposed of in a safe way.
 To clean the floor and all objects contaminated by this material, use water and detergent.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Explosive



Radioactive



Oxidizing

x

x

x

x — Must not be stored together