

## Baker Hughes Flo-Back Prime

INGREDIENTS	CAS NO	%	8HR OEL
GLYCEROL	56-81-5	0.1-1	10 mg/m3
ISOPROPYL ALCOHOL	67-63-0	10-30	983 mg/m3
POLYPROPYLENE GLYCOL	57-55-6	5-10	10 mg/m3
alcohols C12-15 ethoxylated	68131-39-5	10-30	-



UN No: 1993  
 Hazchem Code: 3Y  
 DG Class: 3  
 Subsidiary Risk: **Not Applicable**  
 Packing Group: III  
 Poisons Schedule: **Not Applicable**



## NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

## HEALTH HAZARD INFORMATION



## Acute Health Effects:

Irritating to eyes.  
 Irritating to skin.  
 May cause SENSITISATION by skin contact.

## PRECAUTIONS FOR USE



<b>Appropriate engineering controls:</b>	Local Exhaust Ventilation recommended.
<b>Glasses:</b>	Consider chemical goggles.
<b>Gloves:</b>	1.NEOPRENE 2.NITRILE+PVC 3.PVC
<b>Respirator:</b>	Type AK-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
<b>Storage and Transportation:</b>	Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report. Dispose of this material and its container at hazardous or special waste collection point. Keep out of reach of children. Handle and open container with care.
<b>Fire/Explosion Hazard:</b>	Flammable. Toxic smoke/fumes in a fire. Dispose of this material and its container at hazardous or special waste collection point.

## PROPERTIES



Liquid. Mixes with water. R10R08R19

## EMERGENCY



## FIRST AID

<b>Swallowed:</b>	Give water (if conscious). Seek medical advice.
<b>Eye:</b>	Wash with running water.
<b>Skin:</b>	Remove contaminated clothing. Wash with soap & water.
<b>Inhaled:</b>	Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.
<b>Advice To Doctor:</b>	Treat symptomatically. Severe exposure indicated by respiratory distress/hypotension. Management is essentially supportive.
<b>Fire Fighting:</b>	Water spray/ fog. Foam - alcohol type.
<b>Spills and Disposal:</b>	Eliminate ignition sources. Prevent from entering drains. Contain spillage by any means. Absorb with dry agent. Stop leak if safe to do so. Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water.

## SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Flammable Explosive Toxic Radioactive Oxidizing

x — Must not be stored together