

MULTITREAT 1706 (CORROSION INHIBITOR)

INGREDIENTS	CAS NO	%	8HR OEL
triethanolamine	102-71-6	15-40	5 mg/m3
ethanolamine	141-43-5	3-7	7.5 mg/m3

UN No: **Not Applicable**
 Hazchem Code: **Not Applicable**
 DG Class: **Not Applicable**
 Subsidiary Risk: **Not Applicable**
 Packing Group: **Not Applicable**
 Poisons Schedule: **Not Applicable**



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION



Acute Health Effects:

Harmful: danger of serious damage to health by prolonged exposure through inhalation.
 Irritating to respiratory system and skin.
 Risk of serious damage to eyes.
 May cause SENSITISATION by skin contact.

Chronic Health Effects:

Harmful: danger of serious damage to health by prolonged exposure through inhalation.

* – limited evidence

PRECAUTIONS FOR USE



Appropriate engineering controls:

Local Exhaust Ventilation recommended.

Glasses:

Consider chemical goggles.

Gloves:

1.BUTYL 2.NEOPRENE 3.NITRILE

Respirator:

Type AEK-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Storage and Transportation:

Store in cool, dry, protected area.

Fire/Explosion Hazard:

Toxic smoke/fumes in a fire.

PROPERTIES



Liquid.
 Mixes with water. Combustible.

EMERGENCY



FIRST AID

Swallowed: Give water (if conscious). Seek medical advice.

Eye: Wash with running water (15 mins). Medical attention.

Skin: Remove contaminated clothing. Wash with soap & water.

Inhaled: Fresh air. Rest, keep warm. If breath shallow, give oxygen. Medical attention.

Advice To Doctor: AEK-P

Fire Fighting: Water spray/ fog.

Spills and Disposal: Eliminate ignition sources.
 Absorb with dry agent.
 Stop leak if safe to do so.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Flammable Explosive Radioactive Oxidizing

x x x x

x — Must not be stored together