

HEMPELS BITUMINOUS ALUMINIUM

INGREDIENTS	CAS NO	%	8HR OEL
white spirit	8052-41-3	10-15	790 mg/m3
xylene	1330-20-7	20-30	350 mg/m3
ethylbenzene	100-41-4	2-10	434 mg/m3
no other ingredients specified.	Not Available	NotSpec.	-



UN No: 1263 Hazchem Code: •3Y DG Class: 3

Subsidiary Risk: Not Applicable

Packing Group: III

Poisons Schedule: Not Applicable



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION

















Acute Health Effects: Harmful by inhalation and in contact with skin. Irritating to eyes and skin.

HARMFUL-May cause lung damage if swallowed. Vapours may cause drowsiness and dizziness.

Chronic **Health Effects:** Limited evidence of a carcinogenic effect.

* - limited evidence

PRECAUTIONS FOR USE















Appropriate engineering

Local Exhaust Ventilation recommended.

controls: Glasses:

Consider chemical goggles.

Gloves:

1.PE/EVAL/PE 2.PVA 3.TEFLON

Type A Filter of sufficient capacity. (AS/NZS 1716

Respirator:

& 1715, EN 143:2000 & 149:2001, ANSI Z88 or

national equivalent)

Store in cool, dry, protected area.

Storage and Transportation: Restrictions on Storage apply. Refer to Full Report.

Keep out of reach of children.

Keep away from food, drink and animal feeding stuffs

Fire/Explosion

Hazard:

Flammable.

Environment:

Toxic smoke/fumes in a fire. Harmful to aquatic organisms.

PROPERTIES









Does not mix with water. Sinks in water.Flammable.

EMERGENCY









FIRST AID

Give water (if conscious). Seek medical advice. Swallowed: Do NOT give milk or oil.

Do NOT give alcohol.

Wash with running water. Eye:

Remove contaminated clothing. Wash with soap & Skin:

Fresh air. Rest, keep warm. If breathing shallow, Inhaled:

give oxygen. Medical attention.

Advice To Evaluate for respiratory distress. Consider lavage

with cuffed tube. NO adrenalin. Doctor:

Fire Fighting: Foam.

> Eliminate ignition sources. Prevent from entering drains. Contain spillage by any means.

Spills and Disposal:

Absorb with dry agent. Stop leak if safe to do so.

This material and its container must be disposed of

in a safe way.

To clean the floor and all objects contaminated by this material, use water and detergent.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Explosive



Toxic х



Х



Radioactive Oxidizing

- Must not be stored together