

International Interlac 665 White

INGREDIENTS	CAS NO	%	8HR OEL
naphtha, petroleum, hydrodesulfurised heavy	8032-32-4	25-50	790 mg/m3
silica amorphous	7631-86-9	1-2.5	10 mg/m3
aluminium hydroxide	21645-51-2	1-2.5	-
naphtha petroleum, heavy, hydrotreated	64742-48-9	1-2.5	-



UN No: 1263
 Hazchem Code: 3Y
 DG Class: 3
 Subsidiary Risk: **Not Applicable**
 Packing Group: III
 Poisons Schedule: S5



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION



Acute Health Effects:

Vapours may cause drowsiness and dizziness.

Chronic Health Effects:

Repeated exposure may cause skin dryness and cracking.

* – limited evidence

PROPERTIES



Liquid.
 Does not mix with water.
 Sinks in water. Flammable.

EMERGENCY



FIRST AID

Swallowed:

Give water (if conscious). Seek medical advice.
 Do NOT give milk or oil.
 Do NOT give alcohol.

Eye:

Wash with running water.

Skin:

Remove contaminated clothing. Wash with soap & water.

Inhaled:

Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.

Advice To Doctor:

Treat symptomatically.
 Evaluate for respiratory distress. Consider lavage with cuffed tube. NO adrenalin.

Fire Fighting:

Foam.

Spills and Disposal:

Eliminate ignition sources.
 Prevent from entering drains.
 Contain spillage by any means.
 Absorb with dry agent.
 Stop leak if safe to do so.
 Dispose of this material and its container at hazardous or special waste collection point.
 This material and its container must be disposed of in a safe way.
 To clean the floor and all objects contaminated by this material, use water and detergent.

PRECAUTIONS FOR USE



Appropriate engineering controls:

Local Exhaust Ventilation recommended.

Glasses:

Consider chemical goggles.

Gloves:

PVC chemical resistant type.

Respirator:

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Storage and Transportation:

Store in cool, dry, protected area.
 Restrictions on Storage apply. Refer to Full Report.
 Dispose of this material and its container at hazardous or special waste collection point.
 Keep out of reach of children.

Fire/Explosion Hazard:

Flammable.
 Vapours/gas heavier than air.
 Toxic smoke/fumes in a fire.
 Dispose of this material and its container at hazardous or special waste collection point.

Environment:

Toxic to aquatic organisms.
 May cause long-term adverse effects in the aquatic environment. Use appropriate container to avoid environmental contamination.
 Avoid release to the environment. Refer to special instructions/Safety data sheets.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS

Explosive	Toxic	Radioactive	Oxidizing
x	x	x	x

x — Must not be stored together