

Saudi Industrial Sipco Alkyd Semi Finish

INGREDIENTS	CAS NO	%	8HR OEL
mineral spirit	64475-85-0	15-35	-
alkyd resin	Not Available	30-40	-



UN No: **3082**
 Hazchem Code: **•3Z**
 DG Class: **9**
 Subsidiary Risk: **Not Applicable**
 Packing Group: **III**
 Poisons Schedule: **Not Applicable**



NFPA Rating:

- ▶ **0:** Minimum
- ▶ **1:** Low
- ▶ **2:** Moderate
- ▶ **3:** High
- ▶ **4:** Extreme

HEALTH HAZARD INFORMATION



Acute Health Effects:

Irritating to eyes and skin.
 HARMFUL-May cause lung damage if swallowed.
 Vapours may cause drowsiness and dizziness.

PRECAUTIONS FOR USE



Appropriate engineering controls:

Local Exhaust Ventilation recommended.

Glasses:

Consider chemical goggles.

Gloves:

PVC chemical resistant type.

Respirator:

Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Storage and Transportation:

Store in cool, dry, protected area.
 Restrictions on Storage apply. Refer to Full Report.

Fire/Explosion Hazard:

Flammable.
 Vapours/gas heavier than air.
 Toxic smoke/fumes in a fire.

Environment:

Toxic to aquatic organisms.
 May cause long-term adverse effects in the aquatic environment. Use appropriate container to avoid environmental contamination.
 Avoid release to the environment. Refer to special instructions/Safety data sheets.

PROPERTIES



Liquid.
 Does not mix with water.
 Sinks in water. Flammable.
 Combustible.

EMERGENCY



FIRST AID

Swallowed:

Give water (if conscious). Seek medical advice.
 Do NOT give milk or oil.
 Do NOT give alcohol.

Eye:

Wash with running water.

Skin:

Remove contaminated clothing. Wash with soap & water.

Inhaled:

Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.

Advice To Doctor:

Evaluate for respiratory distress. Consider lavage with cuffed tube. NO adrenalin.

Fire Fighting:

Keep containers cool.
 Foam.

Spills and Disposal:

Eliminate ignition sources.
 Prevent from entering drains.
 Contain spillage by any means.
 Control vapour with water spray/ fog.
 Absorb with dry agent.
 Stop leak if safe to do so.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Explosive Toxic Radioactive Oxidizing
 x x x x

x — Must not be stored together