

Chemetall Ardrex 9D1B Aerosol

INGREDIENTS	CAS NO	%	8HR OEL
ACETONE	67-64-1	30-~60	1185 mg/m3
ISOPROPYL ALCOHOL	67-63-0	10-~30	983 mg/m3
hydrocarbon propellant	68476-85-7.	10-~30	1800 mg/m3
talc	14807-96-6	<10	2.5 mg/m3



UN No: 1950
 Hazchem Code: **Not Applicable**
 DG Class: **2.1**
 Subsidiary Risk: **Not Applicable**
 Packing Group: **Not Applicable**
 Poisons Schedule: **S5**



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION



Acute Health Effects:

Irritating to eyes.
 Vapours may cause drowsiness and dizziness.

Chronic Health Effects:

Repeated exposure may cause skin dryness and cracking.
 * – limited evidence

PROPERTIES



Liquid. Gas. Mixes with water. Extremely flammable.

EMERGENCY



FIRST AID

Skin: Wash with soap & water. Apply cleansing cream.

Fire Fighting: Keep containers cool. Water spray/ fog.

Spills and Disposal: Eliminate ignition sources. Absorb with dry agent. Stop leak if safe to do so. Use only in well ventilated areas. Take precautionary measures against static discharges. Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water.

PRECAUTIONS FOR USE



Gloves: 1.PE/EVAL/PE 2.PVDC/PE/PVDC

Respirator: Type AX Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Storage and Transportation:

Store in cool, dry, protected area. Use only in well ventilated areas. Take precautionary measures against static discharges. Dispose of this material and its container at hazardous or special waste collection point. Keep out of reach of children. Keep in a cool place. Keep container in a well ventilated place. Keep away from heat. Keep away from sources of ignition. No smoking.

Fire/Explosion Hazard:

HIGHLY FLAMMABLE. Toxic smoke/fumes in a fire. Risk of explosion if heated under confinement. Use only in well ventilated areas. Take precautionary measures against static discharges. Dispose of this material and its container at hazardous or special waste collection point. In case of fire and/or explosion, DO NOT BREATHE FUMES.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Explosive Toxic Radioactive Oxidizing
 x x x x

x — Must not be stored together