

## CRC Heavy Duty Silicone Lubricant (Aerosol)

INGREDIENTS	CAS NO	%	8HR OEL
acetone	67-64-1	30-40	1185 mg/m3
hydrocarbon propellant	68476-85-7.	25-35	1800 mg/m3
heptane isomers	Not Available	25-35	-
polydimethylsiloxane	63148-62-9	2-5	-

UN No: **Not Applicable**  
 Hazchem Code: **Not Applicable**  
 DG Class: **Not Applicable**  
 Subsidiary Risk: **Not Applicable**  
 Packing Group: **Not Applicable**  
 Poisons Schedule: **Not Applicable**



## NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

## HEALTH HAZARD INFORMATION



## Acute Health Effects:

Irritating to eyes.  
 HARMFUL-May cause lung damage if swallowed.  
 Vapours may cause drowsiness and dizziness.

## Chronic Health Effects:

Repeated exposure may cause skin dryness and cracking.

\* – limited evidence

## PRECAUTIONS FOR USE



## Appropriate engineering controls:

Local Exhaust Ventilation recommended.

## Glasses:

Consider chemical goggles.

## Gloves:

1.BUTYL/NEOPRENE 2.PE/EVAL/PE

## Respirator:

Type AX-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

## Storage and Transportation:

Store in cool, dry, protected area.

## Fire/Explosion Hazard:

Vapours/gas heavier than air.  
 Toxic smoke/fumes in a fire.

## PROPERTIES



Liquid.In use, may form flammable/ explosive vapour-air mixture  
 Combustible.

## EMERGENCY



## FIRST AID

## Swallowed:

Give water (if conscious). Seek medical advice.  
 Do NOT give milk or oil.  
 Do NOT give alcohol.

## Eye:

Wash with running water.

## Skin:

Remove contaminated clothing. Wash with soap & water.

## Inhaled:

Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.

## Advice To Doctor:

No antidote. Supportive care.  
 Evaluate for respiratory distress. Consider lavage with cuffed tube. NO adrenalin.

## Fire Fighting:

Foam.

## Spills and Disposal:

Spilled liquid has low temperature and evaporates quickly.  
 Eliminate ignition sources.  
 Control vapour with water spray/ fog.  
 Absorb with dry agent.  
 Stop leak if safe to do so.

## SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Explosive Radioactive Oxidizing

x

x

x

x — Must not be stored together