

Dowell High-Temperature Corrosion Inhibitor A270

INGREDIENTS	CAS NO	%	8HR OEL
formic acid	64-18-6	26.6	9.4 mg/m3
METHANOL	67-56-1	1.8	262 mg/m3
METHANOL	67-56-1	-	262 mg/m3



UN No: 2920
 Hazchem Code: •3W
 DG Class: 8
 Subsidiary Risk: 3
 Packing Group: II
 Poisons Schedule: S5



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

PROPERTIES



Liquid. Mixes with water. Corrosive. Acid. Highly flammable.

EMERGENCY



FIRST AID

Swallowed:	Give water (if conscious). URGENT MEDICAL ATTENTION.
Eye:	Wash with running water (15 mins). Medical attention.
Skin:	Flood body with water. Remove contaminated clothing. Wash with water
Inhaled:	Fresh air. Rest, keep warm. If breath shallow, give oxygen. Medical attention.
Advice To Doctor:	Airway problems - 100% O2. Treat burns as thermal. Retract eyelids - irrigate 30 mins. Retract eyelids/ Irrigate 30 mins.
Fire Fighting:	Keep containers cool. Water spray/ fog.
Spills and Disposal:	Eliminate ignition sources. Prevent from entering drains. Contain spillage by any means. Control vapour with water spray/ fog. Absorb with dry agent. Neutralize with soda ash/ lime. Stop leak if safe to do so. Use only in well ventilated areas. Take precautionary measures against static discharges. Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS

Explosive	Toxic	Radioactive	Oxidizing
x	x	x	x

x — Must not be stored together

HEALTH HAZARD INFORMATION



Acute Health Effects:

Harmful if swallowed.
 Causes burns.
 Risk of serious damage to eyes.

PRECAUTIONS FOR USE



Appropriate engineering controls:	Local Exhaust Ventilation recommended.
Glasses:	Consider chemical goggles. Consider full face-shield.
Gloves:	1.BUTYL 2.SARANEX-23 3.TEFLON
Respirator:	Type BAX-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
Storage and Transportation:	Restrictions on Storage apply. Refer to Full Report. Use only in well ventilated areas. Take precautionary measures against static discharges. Dispose of this material and its container at hazardous or special waste collection point. Keep locked up. Keep out of reach of children. Keep away from living quarters. Keep container in a well ventilated place. Keep away from food, drink and animal feeding stuffs. Keep away from sources of ignition. No smoking.
Fire/Explosion Hazard:	HIGHLY FLAMMABLE. Vapours/gas heavier than air. Toxic smoke/fumes in a fire. Attacks metals to liberate hydrogen. Use only in well ventilated areas. Take precautionary measures against static discharges. Dispose of this material and its container at hazardous or special waste collection point. In case of fire and/or explosion, DO NOT BREATHE FUMES.