

BELZONA CERAMIC R METAL (NO.1311)

INGREDIENTS	CAS NO	%	8HR OEL
silica amorphous	7631-86-9	1-5	10 mg/m3
bisphenol A/ diglycidyl ether polymer, high molecular weight	25068-38-6	10-30	-



UN No: 3077 Hazchem Code: 2Z DG Class: 9

Subsidiary Risk: Not Applicable

Packing Group: III Poisons Schedule: S5



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION









Irritating to eyes and skin.

May cause SENSITISATION by skin contact.

PRECAUTIONS FOR USE





Appropriate







engineering controls:	General Exhaust Ventilation adequate.
Glasses:	Consider chemical goggles.
Storage and Transportation:	Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report.
Fire/Explosion Hazard:	Toxic smoke/fumes in a fire.
Environment:	Toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment. Use appropriate container to avoid environmental contamination. Avoid release to the environment. Refer to special instructions/Safety data sheets.

PROPERTIES







Does not mix with water. Sinks in water.Combustible. May form explosive peroxides.

EMERGENCY









FIRST AID

Swallowed:	Rinse mouth with water.
Eye:	Wash with running water.
Skin:	Remove contaminated clothing. Wash with soap & water.
Inhaled:	Fresh air. Rest, keep warm.
Advice To Doctor:	Treat symptomatically.
Fire Fighting:	Keep containers cool. Water spray/ fog.
	Eliminate ignition sources.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS

Prevent from entering drains. Contain spillage by any means.







Pollutant.

x x x — Must not be stored together

Spills and

Disposal: