

## Rocol Layout Ink Spray

INGREDIENTS	CAS NO	%	8HR OEL
acetone	67-64-1	30-50	1185 mg/m3
isopropanol	67-63-0	10-30	983 mg/m3
hydrocarbon propellant	68476-85-7.	30-50	1800 mg/m3



UN No: 1950  
 Hazchem Code: 2Y  
 DG Class: 2.1  
 Subsidiary Risk: **None**  
 Packing Group: **None**  
 Poisons Schedule: **S5**



### NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

### HEALTH HAZARD INFORMATION



**Acute Health Effects:** Irritating to eyes.  
 Vapours may cause drowsiness and dizziness.

**Chronic Health Effects:** Repeated exposure may cause skin dryness and cracking.

\* – limited evidence

### PROPERTIES



Liquid  
 Extremely flammable.

### EMERGENCY



### FIRST AID

**Swallowed:** Give water (if conscious). Seek medical advice.

**Skin:** Wash with soap & water. Apply cleansing cream.

**Fire Fighting:** Keep containers cool. Water spray/ fog.

**Spills and Disposal:** Eliminate ignition sources. Prevent from entering drains. Contain spillage by any means. Absorb with dry agent. Stop leak if safe to do so. Use only in well ventilated areas. Take precautionary measures against static discharges. Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water and detergent.

### PRECAUTIONS FOR USE



**Gloves:** 1.PVDC/PE/PVDC 2.PE/EVAL/PE

**Respirator:** Type AX Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

**Storage and Transportation:** Store in cool, dry, protected area. Use only in well ventilated areas. Take precautionary measures against static discharges. Dispose of this material and its container at hazardous or special waste collection point. Keep out of reach of children. Keep in a cool place. Keep container in a well ventilated place. Keep away from heat. Keep away from sources of ignition. No smoking.

**Fire/Explosion Hazard:** HIGHLY FLAMMABLE. Toxic smoke/fumes in a fire. Risk of explosion if heated under confinement. Use only in well ventilated areas. Take precautionary measures against static discharges. Dispose of this material and its container at hazardous or special waste collection point. In case of fire and/or explosion, DO NOT BREATHE FUMES.

### SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Explosive

x



Toxic

x



Radioactive

x



Oxidizing

x

x — Must not be stored together