

## Akzo Nobel Interlac 665 RAL 1021 Yellow

INGREDIENTS	CAS NO	%	8HR OEL
naphtha, petroleum, hydrodesulfurised heavy	64742-82-1.	35-75	790 mg/m3
naphtha petroleum, heavy, hydrotreated	64742-48-9.	<3	-
methyl ethyl ketoxime	96-29-7	<1	-
zirconium 2-ethylhexanoate	22464-99-9	<0.3	-



UN No: 1263  
 Hazchem Code: 3Y  
 DG Class: 3  
 Subsidiary Risk: **Not Applicable**  
 Packing Group: III  
 Poisons Schedule: S5



## NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

## HEALTH HAZARD INFORMATION



**Acute Health Effects:** May cause SENSITISATION by skin contact. Vapours may cause drowsiness and dizziness.

**Chronic Health Effects:** Limited evidence of a carcinogenic effect. Toxic: danger of serious damage to health by prolonged exposure through inhalation. Possible risk of impaired fertility. Possible risk of harm to the unborn child. Repeated exposure may cause skin dryness and cracking.

\* – limited evidence

## PROPERTIES



Liquid. Does not mix with water. Floats on water. Flammable.

## EMERGENCY



## FIRST AID

**Swallowed:** Give water (if conscious). Seek medical advice. Do NOT give milk or oil. Do NOT give alcohol.

**Eye:** Wash with running water (15 mins). Medical attention.

**Skin:** Remove contaminated clothing. Wash with soap & water.

**Inhaled:** Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.

**Advice To Doctor:** Evaluate for respiratory distress. Consider lavage with cuffed tube. NO adrenalin.

**Fire Fighting:** Foam.

**Spills and Disposal:** Eliminate ignition sources. Prevent from entering drains. Contain spillage by any means. Absorb with dry agent. Stop leak if safe to do so. Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water and detergent.

## PRECAUTIONS FOR USE



**Appropriate engineering controls:** Local Exhaust Ventilation recommended.

**Glasses:** Consider chemical goggles.

**Gloves:** PVC chemical resistant type.

**Respirator:** Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

**Storage and Transportation:** Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report. Dispose of this material and its container at hazardous or special waste collection point. Keep locked up. Keep out of reach of children. Keep away from living quarters.

**Fire/Explosion Hazard:** Flammable. Toxic smoke/fumes in a fire. Dispose of this material and its container at hazardous or special waste collection point. In case of fire and/or explosion, DO NOT BREATHE FUMES.

## SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Flammable Explosive Toxic Radioactive Oxidizing

x

x

x

x

x

x — Must not be stored together