

PLASTIC WOOD

INGREDIENTS	CAS NO	%	8HR OEL
n-butyl acetate	123-86-4	10	713 mg/m3
acetone	67-64-1	30	1185 mg/m3
calcium carbonate	471-34-1	NotSpec.	10 mg/m3

UN No: **Not Applicable**
 Hazchem Code: **Not Applicable**
 DG Class: **Not Applicable**
 Subsidiary Risk: **Not Applicable**
 Packing Group: **Not Applicable**
 Poisons Schedule: **Not Applicable**



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION



Acute Health Effects:	Irritating to eyes. Vapours may cause drowsiness and dizziness.
Chronic Health Effects:	Repeated exposure may cause skin dryness and cracking. * – limited evidence

PRECAUTIONS FOR USE



Appropriate engineering controls:	Local Exhaust Ventilation recommended.
Glasses:	Consider chemical goggles.
Gloves:	1.PE/EVAL/PE 2.BUTYL/NEOPRENE
Respirator:	Type AX Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
Storage and Transportation:	Store in cool, dry, protected area.
Fire/Explosion Hazard:	HIGHLY FLAMMABLE.

PROPERTIES



Does not mix with water.
Sinks in water. Highly flammable.

EMERGENCY



FIRST AID

Swallowed:	Give water (if conscious). Seek medical advice.
Eye:	Wash with running water.
Skin:	Remove contaminated clothing. Wash with soap & water.
Inhaled:	Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.
Advice To Doctor:	No antidote. Supportive care.
Fire Fighting:	Foam.
Spills and Disposal:	Eliminate ignition sources.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS

Explosive	Toxic	Radioactive	Oxidizing
x	x	x	x

x — Must not be stored together