

Liebherr Spezialfett 9610 Plus

INGREDIENTS	CAS NO	%	8HR OEL
di-tert-dodecyl polysulfides	68425-15-0	<10	-
mineral oil	Not avail.	>60	0.1 mg/m3
additives	Not Available	NotSpec.	-
thickener	Not Available	NotSpec.	-

UN No: **Not Applicable**
 Hazchem Code: **Not Applicable**
 DG Class: **Not Applicable**
 Subsidiary Risk: **Not Applicable**
 Packing Group: **Not Applicable**
 Poisons Schedule: **Not Applicable**



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION

PRECAUTIONS FOR USE



Appropriate engineering controls:	General Exhaust Ventilation adequate.
Glasses:	Consider chemical goggles.
Gloves:	LBGV2
Respirator:	Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
Storage and Transportation:	Store in cool, dry, protected area. Dispose of this material and its container at hazardous or special waste collection point. Keep out of reach of children.
Fire/Explosion Hazard:	Toxic smoke/fumes in a fire. Dispose of this material and its container at hazardous or special waste collection point.

PROPERTIES



Liquid. Does not mix with water. Floats on water. Combustible.

EMERGENCY



FIRST AID

Swallowed:	Rinse mouth with water.
Eye:	Wash with running water. For discomfort seek medical advice.
Skin:	Wash with soap
Inhaled:	Fresh air. Rest, keep warm.
Advice To Doctor:	Emesis generally unnecessary. Debride for subcutaneous injection.
Fire Fighting:	Foam.
Spills and Disposal:	Eliminate ignition sources. Absorb with dry agent. Stop leak if safe to do so. Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS

x — Must not be stored together