

Schlumberger Gasblok(*) LT D500

INGREDIENTS	CAS NO	%	8HR OEL
METHANOL	67-56-1	<1	262 mg/m3
hexahydro-1,3,5-tris(hydroxyethyl)triazine	4719-04-4	<1	-
Phosphate Standard Solution 500 mg/l as PO4	7732-18-5	>60	-

UN No: Not Applicable

Hazchem Code: Not Applicable

DG Class: None Subsidiary Risk: None Packing Group: None

Poisons Schedule: Not Applicable



NFPA Rating:

- ▶ 0: Minimum
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION



Acute Health Effects:

May cause SENSITISATION by skin contact.

PRECAUTIONS FOR USE













Appropriate engineering	General Exhaust Ventilation adequate.	
controls:		
Glasses:	Consider chemical goggles.	
Gloves:	1.BUTYL 2.NEOPRENE 3.TEFLON	
Respirator:	Type AX Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)	
Storage and Transportation:	Store in cool, dry, protected area. Dispose of this material and its container at hazardous or special waste collection point. Keep out of reach of children.	
Fire/Explosion Hazard:	Vapours/gas heavier than air. Dispose of this material and its container at hazardous or special waste collection point.	

PROPERTIES





Liquid. Mixes with water. Does not burn.

EMERGENCY







FIRST AID

Swallowed:	Rinse mouth with water.
Eye:	Wash with running water. For discomfort seek medical advice.
Skin:	Remove contaminated clothing. Wash with soap & water.
Inhaled:	Fresh air. Rest, keep warm.
Advice To Doctor:	Treat symptomatically. Decontaminate with ipecac or lavage. Ethanol therapy.
Fire Fighting:	Keep surrounding area cool. Water spray/fog.
Spills and Disposal:	Absorb with dry agent. Stop leak if safe to do so. Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS

x — Must not be stored together