DOW F-78, F-75N

INGREDIENTS	CAS NO	%	8HR OEL
isopropanol	67-63-0	15-40	983 mg/m3
methanol	67-56-1	3-7	262 mg/m3
ethanol	64-17-5	1-5	1880 mg/m3
water	7732-18-5	15-40	-

UN No: **1993**
Hazchem Code: **•3Y**
DG Class: **3**
Subsidiary Risk: **Not Applicable**
Packing Group: **III**
Poisons Schedule: **S5**

NFPA Rating:
▸ **0:** Minimum
▸ **1:** Low
▸ **2:** Moderate
▸ **3:** High
▸ **4:** Extreme

HEALTH HAZARD INFORMATION

| Acute Health Effects: | Harmful by inhalation, in contact with skin and if swallowed.
Irritating to eyes.
Vapours may cause drowsiness and dizziness.
Harmful:possible risk of irreversible effects through inhalation, in contact with skin and if swallowed. |
|---|---|

PRECAUTIONS FOR USE

Appropriate engineering controls:	Local Exhaust Ventilation recommended.
Glasses:	Consider chemical goggles.
Gloves:	1.NEOPRENE 2.NATURALRUBBER
Respirator:	Type AX Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
Storage and Transportation:	Store in cool, dry, protected area.
Restrictions on Storage apply. Refer to Full Report.
Fire/Explosion Hazard:	Flammable.
Toxic smoke/fumes in a fire.
Environment:	Toxic to aquatic organisms.Use appropriate container to avoid environmental contamination.

PROPERTIES

Liquid.
Mixes with water.Flammable.

EMERGENCY

FIRST AID

Swallowed:	Give water (if conscious). Seek medical advice.
Eye:	Wash with running water.
Skin:	Remove contaminated clothing. Wash with soap & water.
Inhaled:	Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.
Fire Fighting:	Water spray/ fog.
Foam - alcohol type.
Spills and Disposal:	Spilled liquid has low temperature and evaporates quickly.
Eliminate ignition sources.
Prevent from entering drains.
Contain spillage by any means.
Control vapour with water spray/ fog.
Absorb with dry agent.
Stop leak if safe to do so.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS

Explosive	Toxic	Radioactive	Oxidizing
x	x	x	x

x — *Must not be stored together*