

Randolph MIL-PRF-81352C 13538 Gloss Acrylic-Gallon

INGREDIENTS	CAS NO	%	8HR OEL
acetone	67-64-1	10	1185 mg/m3
propylene glycol monomethyl ether acetate, alpha-isomer	108-65-6	1	274 mg/m3
titanium dioxide	13463-67-7	0.432	10 mg/m3
4-chlorobenzotrifluoride	98-56-6	60	-



UN No: 1263 Hazchem Code: •3YE

DG Class: 3

Subsidiary Risk: Not Applicable

Packing Group: II

Poisons Schedule: Not Applicable



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION











Irritating to eyes.

Irritating to respiratory system.

Irritating to skin.

Chronic **Health Effects:** May cause CANCER by inhalation.

* - limited evidence

PRECAUTIONS FOR USE





Hazard:

Appropriate engineering







Local Exhaust Ventilation recommended.



controls:	
Glasses:	Consider chemical goggles.
Gloves:	1.BUTYL 2.BUTYL/NEOPRENE 3.PVA
Respirator:	Type AX Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
Storage and Transportation:	Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report. Use only in well ventilated areas. Take precautionary measures against static discharges. Dispose of this material and its container at hazardous or special waste collection point. Keep out of reach of children. Keep container in a well ventilated place. Keep away from sources of ignition. No smoking.
Fire/Explosion	HIGHLY FLAMMABLE. Vapours/gas heavier than air. Toxic smoke/fumes in a fire. Use only in well ventilated areas. Take precautionary measures against static discharges. Dispose of this material

DO NOT BREATHE FUMES.

and its container at hazardous or special waste collection point. In case of fire and/or explosion,

PROPERTIES









Liquid. Does not mix with water. Sinks in water. Highly flammable.

EMERGENCY











FIRST AID

Swallowed:	Give water (if conscious). Seek medical advice.
Eye:	Wash with running water.
Skin:	Remove contaminated clothing. Wash with soap & water.
Inhaled:	Fresh air. Rest, keep warm. If breath shallow, give oxygen. Medical attention.
Fire Fighting:	Keep containers cool. Foam.
	Spilled liquid has low boiling temperature and evaporates quickly. Eliminate ignition sources. Consider evacuation. Prevent from entering drains.

Spills and Disposal: water spray/ fog. Absorb with dry agent. Stop leak if safe to do so. Use only in well ventilated areas. Take precautionary measures against static discharges. Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water and detergent.

Contain spillage by any means. Control vapour with

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS











Explosive x

Toxic

х

Radioactive Oxidizing

- Must not be stored together