

## Champion Cortron RN-661

INGREDIENTS	CAS NO	%	8HR OEL
2-BUTOXYETHANOL	111-76-2	1-10	96.9 mg/m3
METHANOL	67-56-1	1-10	262 mg/m3
benzyl-C12-16-alkyldimethylammonium chloride	68424-85-1	1-10	-
benzyl-C12-16-alkyldimethylammonium chloride	68424-85-1	1-10	-



UN No: 3265  
 Hazchem Code: 2X  
 DG Class: 8  
 Subsidiary Risk: **None**  
 Packing Group: II  
 Poisons Schedule: **Not Applicable**



## NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

## HEALTH HAZARD INFORMATION



## Acute Health Effects:

Harmful by inhalation.  
 Harmful in contact with skin.  
 Harmful if swallowed.  
 Causes severe burns.  
 Very toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.  
 Risk of serious damage to eyes.  
 May cause SENSITISATION by skin contact.

## Chronic Health Effects:

Harmful: danger of serious damage to health by prolonged exposure if swallowed.  
 May cause harm to the unborn child.

\* – limited evidence

## PROPERTIES



Liquid. Corrosive. Acid. Alkaline. R18HAG18R19

## EMERGENCY



## FIRST AID

## Swallowed:

Give water (if conscious). URGENT MEDICAL ATTENTION. Do NOT give milk or oil. Do NOT give alcohol.

## Eye:

Wash with running water (15 mins). Medical attention.

## Skin:

Flood body with water. Remove contaminated clothing. Wash with water

## Inhaled:

Fresh air. Rest, keep warm. If breath shallow, give oxygen. Medical attention.

## Advice To Doctor:

Airway problems - 100% O2. Treat burns as thermal. Retract eyelids - irrigate 30 mins. Retract eyelids/ Irrigate 30 mins. Supportive care. Irrigate eyes with saline. Supportive care. Decontaminate with ipecac or lavage. Ethanol therapy.

## Fire Fighting:

Water spray/ fog.

## Spills and Disposal:

Eliminate ignition sources. Prevent from entering drains. Contain spillage by any means. Absorb with dry agent. Neutralize with soda ash/ lime. Stop leak if safe to do so. Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water and detergent.

## PRECAUTIONS FOR USE



## Appropriate engineering controls:

Local Exhaust Ventilation recommended.

## Glasses:

Consider full face-shield.

## Gloves:

1.BUTYL 2.PE/EVAL/PE 3.TEFLON

## Respirator:

Type BKAX-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

## Storage and Transportation:

Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report. Dispose of this material and its container at hazardous or special waste collection point. Keep locked up. Keep out of reach of children. Keep away from living quarters. Keep away from food, drink and animal feeding stuffs. Handle and open container with care.

## Fire/Explosion Hazard:

Unstable. Toxic smoke/fumes in a fire. Attacks metals to liberate hydrogen. Dispose of this material and its container at hazardous or special waste collection point. In case of fire and/or explosion, DO NOT BREATHE FUMES.

## SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Flammable Explosive Radioactive Oxidizing

x

x

x

x

x — Must not be stored together