

Baker Petrolite DMO-22104

INGREDIENTS	CAS NO	%	8HR OEL
xylene	1330-20-7	10-20	350 mg/m3
naphthalene	91-20-3	<5	52 mg/m3
solvent naphtha petroleum, heavy aromatic	64742-94-5	5-15	-
1,2,4-trimethyl benzene	95-63-6	<5	-



UN No: 1993 Hazchem Code: •3Y DG Class: 3

Subsidiary Risk: Not Applicable

Packing Group: III

Poisons Schedule: Not Applicable

NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION













Harmful by inhalation and in contact with skin. Irritating to eyes and skin.

Vapours may cause drowsiness and dizziness.

Chronic **Health Effects:** Limited evidence of a carcinogenic effect.

* - limited evidence

PRECAUTIONS FOR USE















Appropriate engineering controls:	Local Exhaust Ventilation recommended.
Glasses:	Consider chemical goggles.
Gloves:	1.PE/EVAL/PE 2.PVA 3.VITON
Respirator:	Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
Storage and Transportation:	Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report. Keep out of reach of children. Keep away from food, drink and animal feeding stuffs.
Fire/Explosion Hazard:	Flammable. Toxic smoke/fumes in a fire.
Environment:	Toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment. Use appropriate container to avoid environmental contamination.

instructions/Safety data sheets.

Avoid release to the environment. Refer to special

PROPERTIES









Does not mix with water. Floats on water.Flammable.

EMERGENCY









FIRST AID

Swallowed:	Give water (if conscious). Seek medical advice. Do NOT give milk or oil. Do NOT give alcohol.
Eye:	Wash with running water.
Skin:	Remove contaminated clothing. Wash with soap & water.
Inhaled:	Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.
Advice To Doctor:	Evaluate for respiratory distress. Consider lavage with cuffed tube. NO adrenalin.
Fire Fighting:	Foam.
Spills and	Eliminate ignition sources. Prevent from entering drains. Contain spillage by any means. Absorb with dry agent.

Disposal:

Stop leak if safe to do so. This material and its container must be disposed of

in a safe way. To clean the floor and all objects contaminated by

this material, use water and detergent.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS





Spills and





Explosive x

Toxic Radioactive Oxidizing

Х