

Rust-Oleum Beye 5-GL 4 LB Clear Shellac

INGREDIENTS	CAS NO	%	8HR OEL
ethanol	64-17-5	<60	1880 mg/m3
isopropanol	67-63-0	<5	983 mg/m3



UN No: 1263
 Hazchem Code: •3YE
 DG Class: 3
 Subsidiary Risk: **Not Applicable**
 Packing Group: II
 Poisons Schedule: **Not Applicable**



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION



Acute Health Effects:

Irritating to eyes.

PRECAUTIONS FOR USE



Appropriate engineering controls:

Local Exhaust Ventilation recommended.

Glasses:

Consider chemical goggles.

Gloves:

1.NEOPRENE 2.NITRILE 3.PVC

Respirator:

Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Storage and Transportation:

Store in cool, dry, protected area.
 Restrictions on Storage apply. Refer to Full Report.
 Keep out of reach of children.
 Keep container in a well ventilated place.
 Keep away from sources of ignition. No smoking.

Fire/Explosion Hazard:

HIGHLY FLAMMABLE.
 Vapours/gas heavier than air.
 Toxic smoke/fumes in a fire.
 In case of fire and/or explosion, DO NOT BREATHE FUMES.

PROPERTIES



Liquid. Highly flammable.

EMERGENCY



FIRST AID

Swallowed: Give water (if conscious). Seek medical advice.

Eye: Wash with running water.

Skin: Remove contaminated clothing. Wash with soap & water.


Inhaled: Fresh air. Rest, keep warm.

Advice To Doctor: Treat symptomatically.

Fire Fighting: Keep containers cool.
 Foam.

Spills and Disposal: Eliminate ignition sources.
 Consider evacuation.
 Prevent from entering drains.
 Contain spillage by any means.
 Absorb with dry agent.
 Stop leak if safe to do so.
 This material and its container must be disposed of in a safe way.
 To clean the floor and all objects contaminated by this material, use water and detergent.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS

			
Explosive	Toxic	Radioactive	Oxidizing
x	x	x	x

x — Must not be stored together