

Krylon 1602, Flat Black, 37078, Spray Paint

INGREDIENTS	CAS NO	%	8HR OEL
toluene	108-88-3	32	191 mg/m3
methylene chloride	75-09-2	10	174 mg/m3
xylene	1330-20-7	4	350 mg/m3
acetone	67-64-1	20	1185 mg/m3



UN No: 1950
 Hazchem Code: 2Y
 DG Class: 2.1
 Subsidiary Risk: **Not Applicable**
 Packing Group: **Not Applicable**
 Poisons Schedule: **Not Applicable**



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION



Acute Health Effects:

Harmful if swallowed.
 Irritating to eyes.
 Irritating to skin.
 Vapours may cause drowsiness and dizziness.

Chronic Health Effects:

Limited evidence of a carcinogenic effect.
 Harmful: danger of serious damage to health by prolonged exposure through inhalation.
 Possible risk of harm to the unborn child.
 Repeated exposure may cause skin dryness and cracking.

* – limited evidence

PROPERTIES



Liquid. Gas. Does not mix with water. Floats on water. Extremely flammable.

EMERGENCY



FIRST AID

Swallowed:	Do NOT give milk or oil. Do NOT give alcohol.
Skin:	Wash with soap & water. Apply cleansing cream.
Advice To Doctor:	Evaluate for respiratory distress. Consider lavage with cuffed tube. NO adrenalin. Evaluate for respiratory distress. Consider lavage with cuffed tube. NO adrenalin.
Fire Fighting:	Keep containers cool. Water spray/ fog.
Spills and Disposal:	Eliminate ignition sources. Prevent from entering drains. Contain spillage by any means. Absorb with dry agent. Stop leak if safe to do so. Use only in well ventilated areas. Not recommended for interior use on large surface areas. Take precautionary measures against static discharges. Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water and detergent.

PRECAUTIONS FOR USE



Glasses: Consider chemical goggles.

Gloves: 1.PE/EVAL/PE 2.PVA 3.VITON

Respirator: Type AX Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Storage and Transportation: Store in cool, dry, protected area. Use only in well ventilated areas. Not recommended for interior use on large surface areas. Take precautionary measures against static discharges. Dispose of this material and its container at hazardous or special waste collection point. Keep out of reach of children. Keep container in a well ventilated place. Keep away from food, drink and animal feeding stuffs. Keep away from heat. Keep away from sources of ignition. No smoking.

Fire/Explosion Hazard: HIGHLY FLAMMABLE. Vapours/gas heavier than air. Toxic smoke/fumes in a fire. Risk of explosion if heated under confinement. Use only in well ventilated areas. Not recommended for interior use on large surface areas. Take precautionary measures against static discharges. Dispose of this material and its container at hazardous or special waste collection point. In case of fire and/or explosion, DO NOT BREATHE FUMES.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Explosive	Toxic	Radioactive	Oxidizing
x	x	x	x

x — Must not be stored together