

GE Steamate NA0840

INGREDIENTS	CAS NO	%	8HR OEL
monoethanolamine	141-43-5	15-40	7.5 mg/m3
3-dimethylaminopropylamine	109-55-7	7-13	-



UN No: 3267
 Hazchem Code: 2X
 DG Class: 8
 Subsidiary Risk: **Not Applicable**
 Packing Group: II
 Poisons Schedule: **Not Applicable**



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION



Acute Health Effects:

Harmful by inhalation, in contact with skin and if swallowed.
 Causes severe burns.
 Risk of serious damage to eyes.
 May cause SENSITISATION by skin contact.

PROPERTIES



Mixes with water.
 Corrosive.
 Alkaline/Combustible.

EMERGENCY



FIRST AID

Swallowed:	Give water (if conscious). URGENT MEDICAL ATTENTION.
Eye:	Wash with running water (15 mins). Medical attention.
Skin:	Flood body with water. Remove contaminated clothing. Wash with water
Inhaled:	Fresh air. Rest, keep warm. If breath shallow, give oxygen. Medical attention.
Advice To Doctor:	Supportive care. Irrigate eyes with saline. Supportive care.
Fire Fighting:	Water spray/ fog.
Spills and Disposal:	Eliminate ignition sources. Prevent from entering drains. Contain spillage by any means.

PRECAUTIONS FOR USE



Appropriate engineering controls:	Local Exhaust Ventilation recommended.
Glasses:	Consider full face-shield.
Gloves:	1.BUTYL
Respirator:	Type AEK-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
Storage and Transportation:	Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report.
Fire/Explosion Hazard:	Vapours/gas heavier than air. Toxic smoke/fumes in a fire.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Explosive



Radioactive



Oxidizing

x

x

x

x — Must not be stored together