

Alkyd Paint

INGREDIENTS	CAS NO	%	8HR OEL
distillates, petroleum, light, hydrotreated	64742-47-8	15-40	5 mg/m3

UN No: **Not Applicable**
 Hazchem Code: **Not Applicable**
 DG Class: **Not Applicable**
 Subsidiary Risk: **Not Applicable**
 Packing Group: **Not Applicable**
 Poisons Schedule: **Not Applicable**



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION



Acute Health Effects:

Irritating to skin.
 HARMFUL-May cause lung damage if swallowed.
 Vapours may cause drowsiness and dizziness.

Chronic Health Effects:

Repeated exposure may cause skin dryness and cracking.

* – limited evidence

PROPERTIES



Liquid.
 Does not mix with water. Flammable.
 Combustible.

EMERGENCY



FIRST AID

Swallowed:	Give water (if conscious). Seek medical advice. Do NOT give milk or oil. Do NOT give alcohol.
Eye:	Wash with running water.
Skin:	Remove contaminated clothing. Wash with soap & water.
Inhaled:	Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.
Advice To Doctor:	Evaluate for respiratory distress. Consider lavage with cuffed tube. NO adrenalin.
Fire Fighting:	Foam.
Spills and Disposal:	Eliminate ignition sources. Absorb with dry agent. Stop leak if safe to do so.

PRECAUTIONS FOR USE



Appropriate engineering controls:

Local Exhaust Ventilation recommended.

Glasses:

Consider chemical goggles.

Gloves:

PVC chemical resistant type.

Respirator:

Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Storage and Transportation:

Store in cool, dry, protected area.

Fire/Explosion Hazard:

Flammable.
 Vapours/gas heavier than air.
 Toxic smoke/fumes in a fire.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Explosive Toxic Radioactive Oxidizing

x x x x

x — Must not be stored together