

## Carboline Carboguard 890 Part B

INGREDIENTS	CAS NO	%	8HR OEL
Toluene (Reference Fuel)	108-88-3	<5	191 mg/m3
m-xylene	108-38-3	<5	350 mg/m3
o-xylene	95-47-6	<5	350 mg/m3
p-xylene	106-42-3	<5	350 mg/m3



UN No: 1263  
 Hazchem Code: •3YE  
 DG Class: 3  
 Subsidiary Risk: **Not Applicable**  
 Packing Group: II  
 Poisons Schedule: **Not Applicable**



## NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

## HEALTH HAZARD INFORMATION



## Acute Health Effects:

Harmful by inhalation.  
 Harmful in contact with skin.  
 Harmful if swallowed.  
 Causes burns.  
 Risk of serious damage to eyes.  
 May cause SENSITISATION by skin contact.

## Chronic Health Effects:

Limited evidence of a carcinogenic effect.  
 Harmful: danger of serious damage to health by prolonged exposure through inhalation.  
 \* – limited evidence

## PROPERTIES



Liquid. Highly flammable. May form explosive peroxides.

## EMERGENCY



## FIRST AID

<b>Swallowed:</b>	Give water (if conscious). Seek medical advice.
<b>Eye:</b>	Wash with running water.
<b>Skin:</b>	Remove contaminated clothing. Wash with soap & water.
<b>Inhaled:</b>	Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.
<b>Advice To Doctor:</b>	Evaluate for respiratory distress. Consider lavage with cuffed tube. NO adrenalin.
<b>Fire Fighting:</b>	Keep containers cool. Foam.
<b>Spills and Disposal:</b>	Eliminate ignition sources. Consider evacuation. Prevent from entering drains. Contain spillage by any means. Control vapour with water spray/ fog. Absorb with dry agent. Stop leak if safe to do so. Take precautionary measures against static discharges. Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water and detergent.

## PRECAUTIONS FOR USE



## Appropriate engineering controls:

Local Exhaust Ventilation recommended.

## Glasses:

Consider chemical goggles.

## Gloves:

1. HYPALON 2. VITON/CHLOROBUTYL

## Respirator:

Type BKAX-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

## Storage and Transportation:

Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report. Take precautionary measures against static discharges. Dispose of this material and its container at hazardous or special waste collection point. Keep locked up. Keep out of reach of children. Keep away from living quarters. Keep container in a well ventilated place. Keep away from food, drink and animal feeding stuffs. Keep away from sources of ignition. No smoking. Handle and open container with care.

## Fire/Explosion Hazard:

HIGHLY FLAMMABLE. Toxic smoke/fumes in a fire. Take precautionary measures against static discharges. Dispose of this material and its container at hazardous or special waste collection point. In case of fire and/or explosion, DO NOT BREATHE FUMES.

## SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Explosive	Toxic	Radioactive	Oxidizing
x	x	x	x

x — Must not be stored together