

Ameron Amercoat 52 HS White

| INGREDIENTS | CAS NO | % | 8HR OEL |
|--|------------|-----|-----------|
| ethylbenzene | 100-41-4 | 1-5 | 434 mg/m3 |
| naphtha petroleum, heavy, hydrotreated | 64742-48-9 | 1-5 | - |



UN No: 1263
 Hazchem Code: 3Y
 DG Class: 3
 Subsidiary Risk: **Not Applicable**
 Packing Group: III
 Poisons Schedule: **Not Applicable**



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION

Chronic Health Effects: Limited evidence of a carcinogenic effect.
 * – limited evidence

PRECAUTIONS FOR USE



| | |
|--|---|
| Appropriate engineering controls: | Local Exhaust Ventilation recommended. |
| Glasses: | Consider chemical goggles. |
| Gloves: | PVC chemical resistant type. |
| Respirator: | Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent) |
| Storage and Transportation: | Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report. |
| Fire/Explosion Hazard: | Flammable. Vapours/gas heavier than air. Toxic smoke/fumes in a fire. |

PROPERTIES



Liquid.
 Does not mix with water.
 Sinks in water. Flammable.

EMERGENCY



FIRST AID

| | |
|-----------------------------|---|
| Swallowed: | Rinse mouth with water. |
| Eye: | Wash with running water. For discomfort seek medical advice. |
| Skin: | Wash with soap |
| Inhaled: | Fresh air. Rest, keep warm. |
| Advice To Doctor: | Treat symptomatically. |
| Fire Fighting: | Foam. |
| Spills and Disposal: | Eliminate ignition sources. Prevent from entering drains. Contain spillage by any means. Absorb with dry agent. Stop leak if safe to do so. |

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS

| | | | |
|-----------|-------|-------------|-----------|
| | | | |
| Explosive | Toxic | Radioactive | Oxidizing |
| x | x | x | x |

x — Must not be stored together