

PPG Ca 8800/I 1050 Base Component

INGREDIENTS	CAS NO	%	8HR OEL
amyl methyl ketone	110-43-0	10-30	233 mg/m3
xylene	1330-20-7	1-5	350 mg/m3
methyl isobutyl ketone	108-10-1	0.1-1	205 mg/m3
toluene	108-88-3	0.1-1	191 mg/m3



UN No: 1263
 Hazchem Code: 3Y
 DG Class: 3
 Subsidiary Risk: **Not Applicable**
 Packing Group: III
 Poisons Schedule: **Not Applicable**



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION



Acute Health Effects:

Harmful by inhalation.
 Harmful if swallowed.
 HARMFUL-May cause lung damage if swallowed.

Chronic Health Effects:

Limited evidence of a carcinogenic effect.
 * – limited evidence

PRECAUTIONS FOR USE



Appropriate engineering controls:

Local Exhaust Ventilation recommended.

Glasses:

Consider chemical goggles.

Gloves:

1.TEFLON 2.VITON/CHLOROBUTYL

Respirator:

Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Storage and Transportation:

Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report. Use only in well ventilated areas. Dispose of this material and its container at hazardous or special waste collection point. Keep out of reach of children. Keep away from food, drink and animal feeding stuffs.

Fire/Explosion Hazard:

Flammable. Toxic smoke/fumes in a fire. Use only in well ventilated areas. Dispose of this material and its container at hazardous or special waste collection point.

PROPERTIES



Liquid.Flammable.

EMERGENCY



FIRST AID

Swallowed:

Give water (if conscious). Seek medical advice. Do NOT give milk or oil. Do NOT give alcohol.

Eye:

Wash with running water.

Skin:

Remove contaminated clothing. Wash with soap & water.

Inhaled:

Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.

Advice To Doctor:

Evaluate for respiratory distress. Consider lavage with cuffed tube. NO adrenalin.

Fire Fighting:

Foam.

Spills and Disposal:

Spilled liquid has low boiling temperature and evaporates quickly. Eliminate ignition sources. Prevent from entering drains. Contain spillage by any means. Control vapour with water spray/ fog. Absorb with dry agent. Stop leak if safe to do so. Use only in well ventilated areas. Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water and detergent.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS

Explosive	Toxic	Radioactive	Oxidizing
x	x	x	x

x — Must not be stored together