

BAKER PETROLITE PSK-650

INGREDIENTS	CAS NO	%	8HR OEL
glutaraldehyde	111-30-8	NotSpec.	N/A



UN No: 3265
 Hazchem Code: 2X
 DG Class: 8
 Subsidiary Risk: **Not Applicable**
 Packing Group: II
 Poisons Schedule: **Not Applicable**



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION



Acute Health Effects:

Causes severe burns.
 Risk of serious damage to eyes.
 May cause SENSITISATION by inhalation and skin contact.

PRECAUTIONS FOR USE



Appropriate engineering controls:

Local Exhaust Ventilation recommended.

Glasses:

Consider full face-shield.

Gloves:

PVC chemical resistant type.

Respirator:

Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Storage and Transportation:

Store in cool, dry, protected area.
 Restrictions on Storage apply. Refer to Full Report.
 Keep locked up.
 Keep out of reach of children.
 Keep away from living quarters.

Fire/Explosion Hazard:

Toxic smoke/fumes in a fire.
 Attacks metals to liberate hydrogen.

Environment:

Very toxic to aquatic organisms. Use appropriate container to avoid environmental contamination.
 Avoid release to the environment. Refer to special instructions/Safety data sheets.

PROPERTIES



Liquid.
 Mixes with water.
 Corrosive.
 Acid. Does not burn.

EMERGENCY



FIRST AID

Swallowed:

Give water (if conscious). URGENT MEDICAL ATTENTION.
 Do NOT give milk or oil.
 Do NOT give alcohol.

Eye:

Wash with running water (15 mins). Medical attention.

Skin:

Flood body with water. Remove contaminated clothing. Wash with water

Inhaled:

Fresh air. Rest, keep warm. If breath shallow, give oxygen. Medical attention.

Advice To Doctor:

Airway problems - 100% O2. Treat burns as thermal. Retract eyelids - irrigate 30 mins. Retract eyelids/ Irrigate 30 mins.

Fire Fighting:

Keep surrounding area cool. Water spray/fog.

Spills and Disposal:

Prevent from entering drains.
 Contain spillage by any means.
 Absorb with dry agent.
 Neutralize with soda ash/ lime.
 Stop leak if safe to do so.
 This material and its container must be disposed of in a safe way.
 To clean the floor and all objects contaminated by this material, use water.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Explosive Radioactive Oxidizing

x

x

x

x — Must not be stored together