

MEROPA LUBRICANT 1000

INGREDIENTS	CAS NO	%	8HR OEL
paraffinic distillate, heavy, solvent-dewaxed (severe)	64742-65-0.	99	5 mg/m3
Not Available	Not Available	-	-
antifoam and antiwear agent	Not Available	1	-

UN No: Not Applicable Hazchem Code: Not Applicable DG Class: Not Applicable Subsidiary Risk: Not Applicable Packing Group: Not Applicable Poisons Schedule: Not Applicable



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION



Acute Health Effects:

Vapours may cause drowsiness and dizziness.

PRECAUTIONS FOR USE













Appropriate engineering controls:	General Exhaust Ventilation adequate.
Glasses:	Not normally required
Gloves:	When handling larger quantities: PVC chemical resistant type. Nitrile.
Respirator:	Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
Storage and Transportation:	Store in cool, dry, protected area.
Fire/Explosion Hazard:	Toxic smoke/fumes in a fire.

PROPERTIES







Does not mix with water. Floats on water.A-P

EMERGENCY









FIRST AID

Swallowed:	Give water (if conscious). Seek medical advice.
Eye:	Wash with running water.
Skin:	Remove contaminated clothing. Wash with soap & water.
Inhaled:	Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.
Advice To Doctor:	Emesis generally unnecessary. Debride for subcutaneous injection.
Fire Fighting:	Foam.
Spills and Disposal:	Eliminate ignition sources. Absorb with dry agent. Stop leak if safe to do so.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS

x — Must not be stored together