Chemical Hazard Bulletin

CHB: 1933



5000 ppm

8hr OEL

Ely Supramor 4 Black (Aerosol)

INGREDIENTS

paraffinic distillate, light, catalytic-dewaxed

carbon dioxide

magnetite

hydrocarbon blend dearomatised by catalytic hydrogenation, as

PRECAUTIONS FOR USE

124-38-9

CAS No <u>64742-</u>71-8.







0-60

1-10



GLOVES:

When handling larger quantities:

RESPIRATOR:

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

STORAGE AND TRANSPORTATION:

Store in cool, dry, protected area.

FIRE/EXPLOSION HAZARD:

Toxic smoke/fumes in a fire.

Risk of explosion if heated under confinement.

HEALTH HAZARD INFORMATION



ACUTE HEALTH EFFECTS:

Vapours may cause drowsiness and dizziness.

CHRONIC HEALTH EFFECTS:

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Oxidizin X

X: Must not be stored together

NFPA RATING



NFPA Rating: 0: Minimum, 1: Low, 2: Moderate, 3: High, 4: Extreme



UN No: 1950 Hazchem Code: 2YE DG Class: 2.2

Subsidiary Risk: Not Applicable Packing Group: Not Applicable Poisons Schedule: Not Available

PROPERTIES

Liquid.Gas.Does not mix with water.Floats on water.Does not burn.

EMERGENCY



FIRST AID

SWALLOWED:

Do NOT give milk or oil. Do NOT give alcohol.

SKIN:

Wash with soap & water. Apply cleansing cream.

ADVICE TO DOCTOR:

Emesis generally unnecessary. Debride for subcutaneous injection. Evaluate for respiratory distress. Consider lavage with cuffed tube.

FIRE FIGHTING:

Keep containers cool.

Keep surrounding area cool.Water spray/fog.

SPILLS AND DISPOSAL:

Stop leak if safe to do so.

Prevent from entering drains.

Contain spillage by any means.

Absorb with dry agent

For further information call Environmental Protection: 880-9714 (DH) or 427-0158 (JID)

For proper disposal methods and locations for the chemical or chemical contaminated material, contact the Environmental Engineering Division on 880-9767