

## Exxon Mobil Mobilarma 247

INGREDIENTS	CAS NO	%	8HR OEL
kerosene	8008-20-6	70-80	-
calcium dinonyl naphthalenesulfonate	57855-77-3	1-5	-



UN No: 3082 Hazchem Code: •3Z DG Class: 9

Subsidiary Risk: Not Applicable

Packing Group: III Poisons Schedule: S5



### NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ **3**: High
- ▶ 4: Extreme

# **HEALTH HAZARD INFORMATION**











Irritating to eyes and skin.

HARMFUL-May cause lung damage if swallowed. Vapours may cause drowsiness and dizziness.

#### PRECAUTIONS FOR USE













Appropriate engineering controls:	Local Exhaust Ventilation recommended.
Glasses:	Consider chemical goggles.
Gloves:	PVC chemical resistant type.
Respirator:	Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
Storage and Transportation:	Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report.
Fire/Explosion	Vapours/gas heavier than air.

### **PROPERTIES**





Liquid.

Does not mix with water. Combustible. Can become highly flammable in use.

## **EMERGENCY**









#### **FIRST AID**

Give water (if conscious). Seek medical advice.

Contact Doctor or Poisons Centre. Swallowed:

Do NOT give milk or oil. Do NOT give alcohol.

Eye: Wash with running water.

Remove contaminated clothing. Wash with soap & Skin:

water.

Fresh air. Rest, keep warm. If breathing shallow, Inhaled:

give oxygen. Medical attention.

Evaluate for respiratory distress. Consider lavage **Advice To** 

with cuffed tube. NO adrenalin. Doctor:

Keep containers cool. Fire Fighting:

Foam.

Eliminate ignition sources.

Prevent from entering drains. Spills and Contain spillage by any means. Disposal:

Absorb with dry agent. Stop leak if safe to do so.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS







Explosive Radioactive Oxidizing x x x

- Must not be stored together