

Saudi Industrial Sipoxy Shield 656 Hardener

INGREDIENTS	CAS NO	%	8HR OEL
magnesium silicate hydrate	1343-90-4	15-25	3 mg/m3
2,4,6-tris[(dimethylamino)methyl]phenol	90-72-2	<5	-
benzyl alcohol	100-51-6	2-5	-
cycloaliphatic polyamine, proprietary	Not Available	50-60	-

UN No: Not Applicable Hazchem Code: Not Applicable DG Class: Not Applicable Subsidiary Risk: Not Applicable Packing Group: Not Applicable Poisons Schedule: Not Applicable



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION











Acute Health Effects: Harmful by inhalation.

Irritating to eyes, respiratory system and skin.

PRECAUTIONS FOR USE













Appropriate engineering controls:	Local Exhaust Ventilation recommended.
Glasses:	Consider chemical goggles.
Gloves:	PVC chemical resistant type.
Respirator:	Type AK-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
Storage and Transportation:	Store in cool, dry, protected area.
Fire/Explosion Hazard:	Vapours/gas heavier than air.

PROPERTIES







Does not mix with water. Sinks in water. Does not burn.

EMERGENCY







FIRST AID

Give water (if conscious). Seek medical advice.
Wash with running water.
Remove contaminated clothing. Wash with soap & water.
Fresh air. Rest, keep warm. If breath shallow, give oxygen. Medical attention.
Treat symptomatically.
Keep surrounding area cool. Water spray/fog.
Absorb with dry agent. Stop leak if safe to do so.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS







x x x - Must not be stored together