

## Saudi Industrial Thinner 740

INGREDIENTS	CAS NO	%	8HR OEL
XYLENE	1330-20-7	55-70	350 mg/m3
isobutanol	78-83-1	20-30	152 mg/m3
METHYL ISOBUTYL KETONE	108-10-1	10-20	205 mg/m3

UN No: **Not Applicable**  
 Hazchem Code: **Not Applicable**  
 DG Class: **Not Applicable**  
 Subsidiary Risk: **Not Applicable**  
 Packing Group: **Not Applicable**  
 Poisons Schedule: **Not Applicable**



## NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

## HEALTH HAZARD INFORMATION



## Acute Health Effects:

Harmful by inhalation.  
 Harmful in contact with skin.  
 Irritating to respiratory system.  
 Irritating to skin.  
 Risk of serious damage to eyes.  
 HARMFUL-May cause lung damage if swallowed.  
 Vapours may cause drowsiness and dizziness.

## Chronic Health Effects:

Limited evidence of a carcinogenic effect.  
 Repeated exposure may cause skin dryness and cracking.

\* – limited evidence

## PROPERTIES



Liquid. Does not mix with water. Floats on water. R10HAG18R19

## EMERGENCY



## FIRST AID

## Swallowed:

Give water (if conscious). Seek medical advice. Do NOT give milk or oil. Do NOT give alcohol.

## Eye:

Wash with running water (15 mins). Medical attention.

## Skin:

Remove contaminated clothing. Wash with soap & water.

## Inhaled:

Fresh air. Rest, keep warm. If breath shallow, give oxygen. Medical attention.

## Advice To Doctor:

Evaluate for respiratory distress. Consider lavage with cuffed tube. NO adrenalin.

## Fire Fighting:

Foam.

## Spills and Disposal:

Eliminate ignition sources. Absorb with dry agent. Stop leak if safe to do so. Use only in well ventilated areas. Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water and detergent.

## PRECAUTIONS FOR USE



## Appropriate engineering controls:

Local Exhaust Ventilation recommended.

## Glasses:

Consider chemical goggles.

## Gloves:

1.PE/EVAL/PE 2.PVA 3.TEFLON

## Respirator:

Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

## Storage and Transportation:

Store in cool, dry, protected area. Use only in well ventilated areas. Dispose of this material and its container at hazardous or special waste collection point. Keep out of reach of children. Keep away from food, drink and animal feeding stuffs. Handle and open container with care.

## Fire/Explosion Hazard:

Flammable. Vapours/gas heavier than air. Toxic smoke/fumes in a fire. Use only in well ventilated areas. Dispose of this material and its container at hazardous or special waste collection point.

## Environment:

Harmful to aquatic organisms.

## SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Flammable Explosive Toxic Radioactive Oxidizing Harmful

+

x

x

x

x

+

x — Must not be stored together