

KORP-KOTE

INGREDIENTS	CAS NO	%	8HR OEL
copper	7440-50-8	5-10	0.2 mg/m3
graphite	7782-42-5	10-15	3 mg/m3
molybdenum disulfide	1317-33-5	1-5	2 mg/m3
mica	12001-26-2	1-5	2.5 mg/m3



UN No: 3082
 Hazchem Code: •3Z
 DG Class: 9
 Subsidiary Risk: **Not Applicable**
 Packing Group: III
 Poisons Schedule: **Not Applicable**



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION



Acute Health Effects:

Irritating to eyes.

Chronic Health Effects:

Danger of cumulative effects.

* – limited evidence

PRECAUTIONS FOR USE



Appropriate engineering controls:

General Exhaust Ventilation adequate.

Glasses:

Consider chemical goggles.

Gloves:

PVC chemical resistant type.

Storage and Transportation:

Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report.

Fire/Explosion Hazard:

Vapours/gas heavier than air. Toxic smoke/fumes in a fire.

Environment:

Very toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment. Use appropriate container to avoid environmental contamination. Avoid release to the environment. Refer to special instructions/Safety data sheets.

PROPERTIES



Does not mix with water.
 Sinks in water. Combustible.

EMERGENCY



FIRST AID

Swallowed: Give water (if conscious). Seek medical advice.

Eye: Wash with running water.

Skin: Wash with soap

Inhaled: Fresh air. Rest, keep warm.

Advice To Doctor: Emesis generally unnecessary. Debride for subcutaneous injection. For severe poisoning, administer CaNa2EDTA.

Fire Fighting: Keep containers cool. Foam.

Spills and Disposal: Eliminate ignition sources. Pollutant. Prevent from entering drains. Contain spillage by any means.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Explosive Radioactive Oxidizing

x

x

x

x — Must not be stored together