

Nalco 5151

INGREDIENTS	CAS NO	%	8HR OEL
monoethanolamine	141-43-5	30-60	7.5 mg/m3
3-methoxypropylamine	5332-73-0	5-10	-



UN No: 2735 Hazchem Code: 2X DG Class: 8

Subsidiary Risk: Not Applicable

Packing Group: II

Poisons Schedule: Not Applicable

3 0

NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ **3:** High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION













Acute Health Effects: Harmful by inhalation, in contact with skin and if swallowed.

Causes severe burns.

Risk of serious damage to eyes.

May cause SENSITISATION by skin contact.

PRECAUTIONS FOR USE













Appropriate engineering controls:	General Exhaust Ventilation adequate.
Glasses:	Consider full face-shield.
Gloves:	1.BUTYL 2.BUTYL/NEOPRENE 3.PVA
Respirator:	Type AEK-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
Storage and Transportation:	Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report.
Fire/Explosion Hazard:	Toxic smoke/fumes in a fire.

PROPERTIES





Liquid.
Mixes with water.
Corrosive.
Alkaline.Combustible.

EMERGENCY









FIRST AID

Swallowed:	Give water (if conscious). URGENT MEDICAL ATTENTION.
Eye:	Wash with running water (15 mins). Medical attention.
Skin:	Flood body with water. Remove contaminated clothing. Wash with water
Inhaled:	Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.
Advice To Doctor:	AEK-P
Fire Fighting:	Water spray/ fog.
Spills and Disposal:	Eliminate ignition sources. Prevent from entering drains. Contain spillage by any means. Control vapour with water spray/ fog. Absorb with dry agent. Stop leak if safe to do so.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS







Explosive Radioactive Oxidizing x x x