

Ely Liquid Spray Developer LD3 (Aerosol)

INGREDIENTS	CAS NO	%	8HR OEL
isopropanol	67-63-0	30-50	983 mg/m3
hydrocarbon propellant	68476-85-7.	>50	1800 mg/m3
talc	14807-96-6	5-10	3 mg/m3
silica amorphous	7631-86-9	<1	10 mg/m3



UN No: 1950
 Hazchem Code: 2YE
 DG Class: 2.1
 Subsidiary Risk: **Not Applicable**
 Packing Group: **Not Applicable**
 Poisons Schedule: **Not Applicable**



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION



Acute Health Effects: Irritating to eyes.
 Vapours may cause drowsiness and dizziness.

PRECAUTIONS FOR USE



Glasses:	Consider chemical goggles.
Gloves:	1.NITRILE, PVC 2.PE/EVAL/PE
Respirator:	Type AX Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
Storage and Transportation:	Store in cool, dry, protected area.
Fire/Explosion Hazard:	HIGHLY FLAMMABLE. Vapours/gas heavier than air. Toxic smoke/fumes in a fire. Risk of explosion if heated under confinement.

PROPERTIES



Liquid.
 Gas.
 Does not mix with water.
 Floats on water. Extremely flammable.

EMERGENCY



FIRST AID

Swallowed:	Do NOT give milk or oil. Do NOT give alcohol.
Skin:	Wash with soap & water. Apply cleansing cream.
Advice To Doctor:	Evaluate for respiratory distress. Consider lavage with cuffed tube. NO adrenalin. Severe exposure indicated by respiratory distress/hypotension Managements is essentially supportive.
Fire Fighting:	Keep containers cool. Water spray/ fog. Foam - alcohol type.
Spills and Disposal:	Eliminate ignition sources. Prevent from entering drains. Contain spillage by any means. Absorb with dry agent. Stop leak if safe to do so.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Explosive	Toxic	Radioactive	Oxidizing
x	x	x	x

x — Must not be stored together