

LOCITE THREAD LOCKER 222

INGREDIENTS	CAS NO	%	8HR OEL
isopropyl benzene - cumene	98-82-8	0.1-1	125 mg/m3
titanium dioxide	1317-70-0	0.1-1	10 mg/m3
oleic acid, ethoxylated	9004-96-0	30-60	-
polyethylene glycol dimethacrylate	25852-47-5	30-60	-

UN No: **Not Applicable**
 Hazchem Code: **Not Applicable**
 DG Class: **Not Applicable**
 Subsidiary Risk: **Not Applicable**
 Packing Group: **Not Applicable**
 Poisons Schedule: **Not Applicable**



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION



Acute Health Effects: Irritating to eyes.

Chronic Health Effects: May cause CANCER by inhalation. Repeated exposure may cause skin dryness and cracking.

* – limited evidence

PRECAUTIONS FOR USE



Appropriate engineering controls: Local Exhaust Ventilation recommended.

Glasses: Consider chemical goggles.

Gloves: 1.PE/EVAL/PE 2.TEFLON

Respirator: Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Storage and Transportation: Store in cool, dry, protected area. Keep out of reach of children.

Fire/Explosion Hazard: Toxic smoke/fumes in a fire.

Environment: Harmful to aquatic organisms. May cause long-term adverse effects in the aquatic environment.

PROPERTIES



Liquid.Combustible.

EMERGENCY



FIRST AID

Swallowed: Give water (if conscious). Seek medical advice.

Eye: Wash with running water.

Skin: Wash with soap

Inhaled: Fresh air. Rest, keep warm.

Advice To Doctor: Treat symptomatically.

Fire Fighting: Foam.

Spills and Disposal: Eliminate ignition sources. Absorb with dry agent. Stop leak if safe to do so. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water and detergent.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Explosive Radioactive Oxidizing

x

x

x

x — Must not be stored together