

## Saudi Industrial Sipoxy Shield 285 Off White Base

INGREDIENTS	CAS NO	%	8HR OEL
methyl isobutyl ketone	108-10-1	4-7	205 mg/m3
xylene	1330-20-7	2-5	350 mg/m3
epoxy resin	Not Available	25-40	-

UN No: **Not Applicable**  
 Hazchem Code: **Not Applicable**  
 DG Class: **Not Applicable**  
 Subsidiary Risk: **Not Applicable**  
 Packing Group: **Not Applicable**  
 Poisons Schedule: **Not Applicable**



### NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

### HEALTH HAZARD INFORMATION

### PRECAUTIONS FOR USE



<b>Appropriate engineering controls:</b>	Local Exhaust Ventilation recommended.
<b>Glasses:</b>	Consider chemical goggles.
<b>Gloves:</b>	1.PE/EVAL/PE 2.PVA 3.TEFLON
<b>Respirator:</b>	Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
<b>Storage and Transportation:</b>	Store in cool, dry, protected area. Keep out of reach of children.
<b>Fire/Explosion Hazard:</b>	Flammable. Vapours/gas heavier than air. Toxic smoke/fumes in a fire.

### PROPERTIES



Liquid.  
 Does not mix with water.  
 Sinks in water. Flammable.  
 Combustible.


### EMERGENCY



### FIRST AID

<b>Swallowed:</b>	Give water (if conscious). Seek medical advice. Do NOT give milk or oil. Do NOT give alcohol.
<b>Eye:</b>	Wash with running water.
<b>Skin:</b>	Wash with soap
<b>Inhaled:</b>	Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.
<b>Advice To Doctor:</b>	Evaluate for respiratory distress. Consider lavage with cuffed tube. NO adrenalin.
<b>Fire Fighting:</b>	Foam.
<b>Spills and Disposal:</b>	Eliminate ignition sources. Absorb with dry agent. Stop leak if safe to do so. This material and its container must be disposed of in a safe way.

### SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS

			
Explosive	Toxic	Radioactive	Oxidizing
x	x	x	x

x — Must not be stored together