

### 3M Scotch-Weld Neoprene High Performance Contact Adhesive EC-1357, Grey-Green

INGREDIENTS	CAS NO	%	8HR OEL
naphtha petroleum, light solvent-refined	64741-84-0	30-50	5 mg/m3
n-hexane	110-54-3	5-20	72 mg/m3
toluene	108-88-3	3-7	191 mg/m3
methyl ethyl ketone	78-93-3	7-13	445 mg/m3



UN No: 1133  
 Hazchem Code: \*3YE  
 DG Class: 3  
 Subsidiary Risk: **Not Applicable**  
 Packing Group: II  
 Poisons Schedule: S5



#### NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

#### HEALTH HAZARD INFORMATION



##### Acute Health Effects:

Irritating to eyes.  
 Irritating to skin.  
 May cause SENSITISATION by skin contact.  
 Vapours may cause drowsiness and dizziness.

##### Chronic Health Effects:

Harmful: danger of serious damage to health by prolonged exposure through inhalation.  
 Possible risk of impaired fertility.  
 Possible risk of harm to the unborn child.  
 Repeated exposure may cause skin dryness and cracking.

\* – limited evidence

#### PRECAUTIONS FOR USE



##### Appropriate engineering controls:

Local Exhaust Ventilation recommended.

##### Glasses:

Consider chemical goggles.

##### Gloves:

1.PVDC/PE/PVDC 2.VITON 3.PVA

##### Respirator:

Type AX Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

##### Storage and Transportation:

Store in cool, dry, protected area.  
 Restrictions on Storage apply. Refer to Full Report.  
 Not recommended for interior use on large surface areas.  
 Take precautionary measures against static discharges.  
 Dispose of this material and its container at hazardous or special waste collection point.  
 Keep out of reach of children.  
 Keep container in a well ventilated place.  
 Keep away from sources of ignition. No smoking.

##### Fire/Explosion Hazard:

HIGHLY FLAMMABLE.  
 Vapours/gas heavier than air.  
 Toxic smoke/fumes in a fire.  
 Not recommended for interior use on large surface areas.  
 Take precautionary measures against static discharges.  
 Dispose of this material and its container at hazardous or special waste collection point.  
 In case of fire and/or explosion, DO NOT BREATHE FUMES.

#### PROPERTIES



Liquid. Highly flammable.

#### EMERGENCY



#### FIRST AID

##### Swallowed:

Give water (if conscious). Seek medical advice.  
 Do NOT give milk or oil.  
 Do NOT give alcohol.

##### Eye:

Wash with running water.

##### Skin:

Remove contaminated clothing. Wash with soap & water.

##### Inhaled:

Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.

##### Fire Fighting:

Keep containers cool.  
 Foam.

##### Spills and Disposal:

Spilled liquid has low boiling temperature and evaporates quickly.  
 Eliminate ignition sources.  
 Consider evacuation.  
 Prevent from entering drains.  
 Contain spillage by any means.  
 Control vapour with water spray/ fog.  
 Absorb with dry agent.  
 Stop leak if safe to do so.  
 Not recommended for interior use on large surface areas.  
 Take precautionary measures against static discharges.  
 Dispose of this material and its container at hazardous or special waste collection point.  
 This material and its container must be disposed of in a safe way.  
 To clean the floor and all objects contaminated by this material, use water and detergent.

#### SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Explosive Toxic Radioactive Oxidizing

x x x x

x — Must not be stored together