

Magnaflux White Contrast Paint WCP-2

INGREDIENTS	CAS NO	%	8HR OEL
acetone	67-64-1	60-100	1185 mg/m3
carbon dioxide	124-38-9	9	9000 mg/m3
titanium dioxide	13463-67-7	10-30	10 mg/m3



UN No: 1950
 Hazchem Code: **Not Applicable**
 DG Class: 2.1
 Subsidiary Risk: **Not Applicable**
 Packing Group: **Not Applicable**
 Poisons Schedule: **Not Applicable**



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION



Acute Health Effects: Irritating to eyes.
 Vapours may cause drowsiness and dizziness.

Chronic Health Effects: May cause CANCER by inhalation.
 Repeated exposure may cause skin dryness and cracking.

* – limited evidence

PRECAUTIONS FOR USE



Glasses: Consider chemical goggles.

Gloves: 1.PE/EVAL/PE 2.PVDC/PE/PVDC

Respirator: Type AX Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Storage and Transportation: Store in cool, dry, protected area. Use only in well ventilated areas. Take precautionary measures against static discharges. Dispose of this material and its container at hazardous or special waste collection point. Keep out of reach of children. Keep container in a well ventilated place. Keep away from heat. Keep away from sources of ignition. No smoking.

Fire/Explosion Hazard: HIGHLY FLAMMABLE. Vapours/gas heavier than air. Toxic smoke/fumes in a fire. Risk of explosion if heated under confinement. Use only in well ventilated areas. Take precautionary measures against static discharges. Dispose of this material and its container at hazardous or special waste collection point. In case of fire and/or explosion, DO NOT BREATHE FUMES.

PROPERTIES



Liquid. Gas. Mixes with water. Extremely flammable.

EMERGENCY



FIRST AID

Swallowed:	Give water (if conscious). URGENT MEDICAL ATTENTION.
Skin:	Wash with soap & water. Apply cleansing cream.
Advice To Doctor:	No antidote. Supportive care.
Fire Fighting:	Keep containers cool. Water spray/ fog.
Spills and Disposal:	Spilled liquid has low boiling temperature and evaporates quickly. Eliminate ignition sources. Prevent from entering drains. Contain spillage by any means. Control vapour with water spray/ fog. Absorb with dry agent. Stop leak if safe to do so. Use only in well ventilated areas. Take precautionary measures against static discharges. Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS

Explosive	Toxic	Radioactive	Oxidizing
x	x	x	x

x — Must not be stored together