

Sherwin-Williams MIL-PRF-22750G Type LI 2K High Solids Epoxy Topcoat Part A Seafoam Green 24533 Q2128, Seafoam Green 24533

INGREDIENTS	CAS NO	%	8HR OEL
methyl ethyl ketone	78-93-3	13	445 mg/m3
amyl methyl ketone	110-43-0	4	233 mg/m3
silica crystalline - quartz	14808-60-7	21	mg/m3
calcium carbonate	1317-65-3	20	10 mg/m3



UN No: 1263
 Hazchem Code: •3YE
 DG Class: 3
 Subsidiary Risk: **Not Applicable**
 Packing Group: II
 Poisons Schedule: **Not Applicable**



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION



Acute Health Effects:

Irritating to respiratory system.
 Irritating to skin.
 Risk of serious damage to eyes.
 May cause SENSITISATION by skin contact.

Chronic Health Effects:

Limited evidence of a carcinogenic effect.
 Harmful: danger of serious damage to health by prolonged exposure through inhalation.
 Repeated exposure may cause skin dryness and cracking.

* – limited evidence

PROPERTIES



Liquid. Highly flammable.

EMERGENCY



FIRST AID

Swallowed:	Give water (if conscious). URGENT MEDICAL ATTENTION.
Eye:	Wash with running water (15 mins). Medical attention.
Skin:	Remove contaminated clothing. Wash with soap & water.
Inhaled:	Fresh air. Rest, keep warm. If breath shallow, give oxygen. Medical attention.
Advice To Doctor:	Treat symptomatically.
Fire Fighting:	Keep containers cool. Foam.

PRECAUTIONS FOR USE



Appropriate engineering controls:

Local Exhaust Ventilation recommended.

Glasses:

Consider chemical goggles.

Gloves:

1.TEFLON 2.PE/EVAL/PE 3.PVA

Respirator:

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Storage and Transportation:

Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report. Take precautionary measures against static discharges. Dispose of this material and its container at hazardous or special waste collection point. Keep out of reach of children. Keep container in a well ventilated place. Keep away from sources of ignition. No smoking.

Fire/Explosion Hazard:

HIGHLY FLAMMABLE. Vapours/gas heavier than air. Toxic smoke/fumes in a fire. Take precautionary measures against static discharges. Dispose of this material and its container at hazardous or special waste collection point. In case of fire and/or explosion, DO NOT BREATHE FUMES.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Explosive	Toxic	Radioactive	Oxidizing
x	x	x	x

x — Must not be stored together