

Dow Corning 733 Glass & Metal Sealant Clear

INGREDIENTS	CAS NO	%	8HR OEL
acetic acid glacial	64-19-7	NotSpec.	25 mg/m3
methanol	67-56-1	NotSpec.	262 mg/m3
aluminium	7429-90-5	NotSpec.	5 mg/m3
silica amorphous	7631-86-9	8-9	10 mg/m3

UN No: **Not Applicable**
 Hazchem Code: **Not Applicable**
 DG Class: **Not Applicable**
 Subsidiary Risk: **Not Applicable**
 Packing Group: **Not Applicable**
 Poisons Schedule: **Not Applicable**



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION



Chronic Health Effects:

May cause CANCER by inhalation.
 * – limited evidence

PRECAUTIONS FOR USE



Appropriate engineering controls:	Local Exhaust Ventilation recommended.
Glasses:	Consider chemical goggles.
Gloves:	1.NITRILE+PVC 2.PE 3.TEFLON
Respirator:	Type BAX-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
Storage and Transportation:	Store in cool, dry, protected area. Dispose of this material and its container at hazardous or special waste collection point. Keep out of reach of children.
Fire/Explosion Hazard:	Toxic smoke/fumes in a fire. Dispose of this material and its container at hazardous or special waste collection point.

PROPERTIES



Liquid.Combustible.

EMERGENCY



FIRST AID

Swallowed:	Rinse mouth with water.
Eye:	Wash with running water. For discomfort seek medical advice.
Skin:	Wash with soap
Inhaled:	Fresh air. Rest, keep warm.
Advice To Doctor:	Decontaminate with ipecac or lavage. Ethanol therapy.
Fire Fighting:	Foam.
Spills and Disposal:	Eliminate ignition sources. Absorb with dry agent. Stop leak if safe to do so. Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water and detergent.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS

x — Must not be stored together