

Akzo Nobel Interzinc 52 Part B Tropical

INGREDIENTS	CAS NO	%	8HR OEL
xylene	1330-20-7	10-25	350 mg/m3
naphtha petroleum, light aromatic solvent	64742-95-6	10-25	-
n-butanol	71-36-3	10-25	N/A
tall oil/ triethylenetetramine polyamides	68082-29-1	25-50	-



UN No: 1263 Hazchem Code: •3Y DG Class: 3

Subsidiary Risk: Not Applicable

Packing Group: III Poisons Schedule: \$5



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION













Acute Health Effects: Irritating to eyes and skin.

HARMFUL-May cause lung damage if swallowed. Vapours may cause drowsiness and dizziness.

Chronic **Health Effects:** May cause CANCER.

* - limited evidence

PRECAUTIONS FOR USE















Appropriate engineering controls:	Local Exhaust Ventilation recommended.
Glasses:	Consider chemical goggles.
Gloves:	1.PE/EVAL/PE 2.PVA 3.TEFLON
Respirator:	Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
Storage and Transportation:	Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report. Keep out of reach of children. Keep away from food, drink and animal feeding stuffs.
Fire/Explosion Hazard:	Flammable. Vapours/gas heavier than air. Toxic smoke/fumes in a fire.
Environment:	Toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment. Use appropriate container to avoid environmental contamination. Avoid release to the environment. Refer to special

instructions/Safety data sheets.

PROPERTIES







Liquid.

Does not mix with water.Flammable.

EMERGENCY









FIRST AID

Swallowed:	Give water (if conscious). Seek medical advice. Do NOT give milk or oil. Do NOT give alcohol.
Eye:	Wash with running water.
Skin:	Remove contaminated clothing. Wash with soap & water.
Inhaled:	Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.
Advice To Doctor:	Evaluate for respiratory distress. Consider lavage with cuffed tube. NO adrenalin.
Fire Fighting:	Foam.
	Eliminate ignition sources. Prevent from entering drains.

Absorb with dry agent. Spills and Disposal:

Stop leak if safe to do so. This material and its container must be disposed of

Contain spillage by any means.

in a safe way.

To clean the floor and all objects contaminated by this material, use water and detergent.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Explosive



Toxic



Х



Radioactive Oxidizing

X